

2-2 Advantages of a subsurface dam

Compared with a surface dam, a subsurface dam has the following advantages:

(1) A water storage system without land submergence

A subsurface dam does not submerge land area in contrast with a surface dam because it stores water under ground. Therefore, it does not seriously damage the environment, nor does it cause social problems such as the forced migration of the local people.

(2) Prevention of evaporation of reserved water

A subsurface dam does not lose reserved water by evaporation because water is stored under ground and there is very little evaporation, in contrast with a surface dam that often loses a significant amount of reserved water due to evaporation in the dry season in arid or semi-arid areas.

(3) Clean, safe water

Reserved water using a subsurface dam is of fairly good quality because it is stored under ground, and it can be used like ordinary well water, in contrast with reserved water using a surface dam that tends to proliferate parasites, anopheles that transmit malaria, and germs, and requires purification for domestic use.

(4) A stable, secure dam

In general, a subsurface dam is more stable than a surface dam from the viewpoint of dynamics because it is buried under ground, and thus does not need maintenance. Even if it breaks, there is no damage to the downstream area because the breakage occurs under ground.

(5) Utilization of renewable resources

Shallow groundwater consumed via a subsurface dam system is renewable because it is recharged with rainfall. Therefore, a subsurface dam does not exhaust water resources.

2-3 Disadvantages of a subsurface dam

However, it is necessary to note that a subsurface dam also has the following disadvantages:

(1) Difficulties in site selection

Contrary to a surface dam whose site conditions can be examined by visual inspection, surveys for site selection and calculating the water storage capacity of a subsurface dam rely on estimates of underground geological structures.

(2) Low effectiveness of water storage

In case of a subsurface dam, water is stored in the pores of geological strata. Therefore, the volume of reserved water is determined by the volume of those pores (effective porosity), and reaches only 10 to 30% of the volume of the reservoir layer.

(3) Interception of downstream groundwater flow

A subsurface dam may prevent downstream groundwater flow, and exhausts groundwater in the downstream area. However, groundwater in the downstream area is not always recharged only with groundwater from the dam site area. It is also possible to design a dam with a structure that allows some of the reserved water to drain. Therefore, this problem can be avoided by appropriate site selection that considers the mechanism of groundwater flow, or