令和5年度 インドジャル・シャクティ省との協力覚書に係る 第1回会議体会合及びセミナー開催業務

報告書

令和6年3月

環境省廃棄物適正処理推進課浄化槽推進室 公益財団法人日本環境整備教育センター

目次

第	1 章 業務概要	1
	1.1. 目的	1
	1.2. 実施事項	
	1.2.1. 第1回会議体会合の開催	
	1.2.2. セミナーの開催	
	1.2.4. 打合せ	
	1.2.4. 打日已	1
	1.3. 実施体制	2
	1.4. 業務実施スケジュール	2
第	2 章 第1回会議体会合の開催	3
	2.1. 会議体構成メンバー表及び共同作業計画書の作成	3
	2.2. 第 1 回会議体会合のプログラムの作成	4
	2.3. 第 1 回会議体会合の開催	4
	2.3.1. 開催概要	4
	2.3.2. 有識者への謝金の支払い・同時通訳者の傭上	5
	2.3.3. 第1回会議体会合議事要旨	5
第	3 章 セミナーの開催	14
	3.1. セミナーの詳細プログラムの作成	14
	3.2. セミナーの開催	14
	3.2.1. 開催概要	14
	3.2.2. 有識者への謝金の支払い・同時通訳者の傭上	17
	3.2.3. セミナーにおける質疑応答	17
第	4 章 来期の共同作業に関する調整	18
第	5 章 環境省担当官との打合せ	19
	5.1. 第1回打合せ	19
	5.2. 第 2 回打合せ	21

	5.3. 第3回打合せ	22
	5.4. 第 4 回打合せ	23
第	6 章 資料編	25
	6.1. 最終版の共同作業計画書	25
	6.2. 第1回会議体会合プログラム	30
	6.3. 第1回会議体会合における発表資料	34
	6.3.1. ジャル・シャクティ省の紹介	34
	6.3.2. インド側協賛メンバー Arvind Envisol Ltd.による発表	36
	6.3.3. インド側協賛メンバー Sintex BAPL Ltd.による発表	40
	6.3.4. インド側協賛メンバー Daiki Axis India Pvt. Ltd.による発表	48
	6.3.5. 日本側協賛メンバー クボタ浄化槽システム株式会社による発表	53
	6.3.6. 日本側協賛メンバー フジクリーン工業株式会社による発表	57
	6.3.7. 日本側協賛メンバー 株式会社ダイキアクシスによる発表	61
	6.4. セミナープログラム	64
	6.5. セミナーにおける発表資料	66
	6.5.1. インド側(NMCG)のセミナー発表資料(Current Status of Domestic Wastewater Treatment & Management (for centralized and decentralized treatment system) in India)	66
	6.5.2. 日本側環境省のセミナー発表資料(Current Status of Domestic Wastewater Treatment and its Management for Centralized and Decentralized Treatment System in Japan)	
	6.5.3. 日本側環境省のセミナー発表資料(Legal System of Decentralized Domestic Wastewater Treatment Management in Japan including the Johkasou Act)	
	6.5.4. JECES のセミナー発表資料(Operation and maintenance, cleaning, inspection, license and sludge management for Johkasou)	75
	6.5.5. フジクリーン工業株式会社のセミナー発表資料 (Structure, function and performance evaluation testing system for the Johkasou)	78
	6.5.6. クボタ浄化槽システム株式会社のセミナー発表資料(Estimation method of Population Equivalent (PE))	81
	6.5.7. 株式会社ダイキアクシスのセミナー発表資料(Installation work of Johkasou)	84
	6.6. セミナーにおける質疑応答	90
	6.7. セミナー終了後に日本側会議体メンバーから受領した質問	96

第1章 業務概要

1.1. 目的

令和元年 12 月にインド・デリーにて浄化槽海外セミナーが開催され、その際にジャル・シャクティ省から浄化槽に関する協力覚書締結に関する要望が出された。それ以降、在インド日本大使館と連携してジャル・シャクティ省と協議を重ね、令和 4 年 3 月に日本国環境省とジャル・シャクティ省との間で公共水域の水環境保全と公衆衛生の向上を目的とした浄化槽を活用した分散型生活排水管理に関する協力覚書を締結した(本協力覚書に基づき、日本国環境省とインド共和国ジャル・シャクティ省について、以下、個別に「日本側」、「インド側」といい、総称して「両側」という)。

それ以降、インド側と日本側は協議を重ね、協力覚書に基づく推進母体である会議体構成メンバー表、 今後の協力実施内容を記載した共同作業計画書、共同作業計画書の添付資料として、初回の共同作業 となるセミナーのプログラム案等のドラフトを作成したところである。

そこで本業務では、これら関連書類を完成させ、第1回会議体会合を開催して会議体構成メンバーからこれら書類の承認を得る。次いで、セミナーの議事次第の詳細を詰め、それに基づいたセミナーを開催することを目的とする。

1.2. 実施事項

1.2.1. 第1回会議体会合の開催

- (ア)会議体メンバーと協賛メンバーが記載された会議体構成メンバー表の日本側メンバー部分と共同作業計画書を日本側とインド側に協議の上、最終版を作成した。
- (イ) 開催日時、開催方法、司会者、詳細議事次第等の項目を含む第1回会議体会合のプログラムを 日本側とインド側との協議を踏まえて作成した。
- (ウ) プログラムに基づき第1回会議体会合をオンライン開催した。今後の協力実施内容を記載した 共同作業計画書の承認を得て次の推進項目であるセミナー開催に繋げた。

1.2.2. セミナーの開催

- (ア) 開催日時、開催方法、司会者、発表テーマ、発表者等の詳細を含む詳細プログラムを、日本側と インド側との協議を踏まえて作成した。
- (イ) 第1回会議体会合で承認された共同作業計画書及びセミナーのプログラム案を基にセミナーを オンライン開催した。

1.2.3. 来期の共同作業に関する調整

来期の共同作業に関し、環境省担当官との協議を踏まえつつ、あらためてインド側の意向確認、開催に当たっての方向性や実施内容等に関してインド側との確認や調整を行った。

1.2.4. 打合せ

上記 1.2.1~1.2.3 の業務の実施にあたり、環境省担当官との打合せを 4 回実施した。

1.3. 実施体制

本業務の実施体制を図 1に示す。




図 1 インドジャル・シャクティ省との協力覚書に係る第1回会議体会合及びセミナー開催業務の 実施体制

1.4. 業務実施スケジュール

本業務の実施スケジュールを表 1に示す。

表 1 業務実施スケジュール

4K Wir ele pin		2023年(令和5年)							2024年(令和6年)				
	業務内容		5月	6月					11月		1月		3月
1	.第1回会議体会合の開催												
	(1) 会議体構成メンバー表及び共同作業計画書の作成					●作月	芃		●修正				
	(2) 第1回会議体会合のプログラムの作成					●作月	芃		●修正				
	(3) 第1回会議体会合の開催					←	開催に同	可けた準	備→ ●	〔11/28〕 会合の	第1回会 開催	議体	
2	セミナーの開催												
	(1) セミナーの詳細プログラムの作成					●作.	戓			●修正			
	(2) セミナーの開催					←		催に向い	た準備-	→ ●	(12/19) の開催	セミナー	
3	来期の共同作業に関する調整												
	(2) インド側の意向確認・調整										来期に認・調		
4	環境省担当官との打合せ					•			•	••			
5	報告書の作成及び印刷											報告書の 成→納	品(3/22)

第2章 第1回会議体会合の開催

2.1. 会議体構成メンバー表及び共同作業計画書の作成

第1回会議体会合の開催に先立ち、会議体メンバーと協賛メンバーが記載された会議体構成メンバー表の日本側メンバーと共同作業計画書を、環境省担当官とインド側に協議の上、作成した。環境省担当官と協議の上、次の3名の有識者に対して、日本側会議体メンバーへの就任を依頼し、承諾を得た。

有識者である河村氏は衛生工学及び浄化槽分野の専門家であり、これまで環境省浄化槽推進室の海外案件に座長やパネリストとして参画するなど、アジアの公衆衛生問題と浄化槽事情に精通している。同じく有識者である春日氏は、環境工学分野を専門とし、特に環境微生物学をテーマとした研究を多く手掛けているほか、日越大学への赴任経験など海外での研究実績も多く有する。また同じく蛯江氏は、途上国での分散型汚水処理装置の国際規格化の推進、アジア共通の分散型汚水処理装置の性能試験法の実現に向けた研究プログラムなど、浄化槽の国際展開に係る研究の中心メンバーとして活動実績が多い。

日本側協賛メンバーについては、(一社) 浄化槽システム協会を通して浄化槽メーカー各社に周知を行い、4 社が参画することになった。このほか、海外展開の実績等を考慮のうえ、インドで分散型汚水処理施設の維持管理実績を有する株式会社日吉に日本側協賛メンバーへの就任を依頼し、了承を得た。日本側会議体メンバー及び日本側協賛メンバーについて表 2 及び表 3 に示す。

なお、共同作業計画書(Joint Working Program)については、環境省担当官やインド側と協議のうえ最終案を作成し、2023年11月29日に開催された第1回会議体会合において審議したところ、一部修正があった。この修正を反映した最終版の共同作業計画書については資料編6.1.に示した。

	氏名	備考			
室長	沼田 正樹	環境省			
指導普及係長	佐藤 亮真	環境省			
環境専門調査員	ホワン ティー マイ	環境省			
教授)	河村 清史	有識者			
先端科学技術研究センター)	春日 郁朗	有識者			
開発法人国立環境研究所資源循環領域	蛯江 美孝	有識者			
廃棄物処理処分技術研究室主幹研究員)					
使館 一等書記官	永井 弥穂子	大使館			
# E	指導普及係長 環境専門調査員 教授) 先端科学技術研究センター) 開発法人国立環境研究所資源循環領域 術研究室主幹研究員)	旨導普及係長佐藤 亮真環境専門調査員ホワン ティー マイ教授)河村 清史先端科学技術研究センター)春日 郁朗開発法人国立環境研究所資源循環領域蛯江 美孝術研究室主幹研究員)			

表 2 日本側会議体メンバー

表 3 日本側協賛メンバー

所属	氏名	所属先の海外展開状況
株式会社ハウステック	塚本 幸二	ハンガリー国において浄化槽普及に向けた調査(環境
		省業務)を実施した。
株式会社日吉	松井 和彦	インドにおいて生活排水処理施設の総合維持管理に関
		する JICA 事業を実施した。
株式会社ダイキアクシス	佐伯 和男	インド、インドネシアで浄化槽の生産・販売を行い、
		アジア諸国、アフリカにも事業展開している。
クボタ浄化槽システム株式会社	北井 良人	中国、ベトナム、ミャンマーなど海外で多くの浄化槽
		販売実績を持つ。
フジクリーン工業株式会社	田畑 洋輔	主にアメリカ、オーストラリア、欧州を中心に浄化槽
		の販売事業を展開している。

2.2. 第1回会議体会合のプログラムの作成

開催日時、開催方法、司会者、詳細議事次第等の項目を含む第1回会議体会合のプログラムを環境 省担当官及びインド側との協議を踏まえて作成した。また、仕様書 3.2.(1)に示されているセミナーの プログラム案について、環境省担当官やインド側との協議を踏まえ修正し、第1回会議体会合の際に 議事の1つとして取り上げ、両側が協議を行った。

第1回会議体会合のプログラムについて資料編6.2. に示す。

2.3. 第1回会議体会合の開催

2.3.1. 開催概要

第1回会議体会合を2023年11月29日にオンラインにて開催した。開催概要を表4に示す。

表 4 第1回会議体会会の開催概要

	衣 4 第1四云碳件云盲の開催傚安							
日	時	2023年11月29日 日本時間16:00~18:00 (インド時間12:30~14:30)						
場	所	インド側:NMCG 会議室(National Mission for Clean Ganga, Ministry of Jal Shakti)						
		日本側:日本環境整備教育センター(JECES) 4F 会議室						
		Zoom (Web 会議システム) の Webinar を使用しインド側会場と日本側会場を接続した。						
議	題	1. Introduction on Both sides of Management Council members cum Approval of						
		Associate members (両側の第1回会議体メンバー紹介及び協賛メンバーの承認)						
		2. Keynote Speeches (from both sides) 基調演説(両側)						
		3. Approve the Joint Working Program and the 1st Seminar program(共同作業計画書及び第1回セミナーのプログラムの承認)						
		4. Presentation from the Associate members of both the sides(両側の協賛メンバーによる発表)						

先ず初めに議題 1 として、ジャル・シャクティ省 国家ガンジス川浄化ミッション (National Mission for Clean Ganga, Ministry of Jal Shakti, 以下、NMCG) の Deputy Secretary (課長1) である Shri Dheeraj Joshi (シュリ ディーラジュ ジョシ) 氏、そして環境省 環境再生・資源循環局 廃棄物適正 処理推進課 浄化槽推進室 指導普及係長の佐藤 亮真 氏より、インド側、日本側のそれぞれの会議体メンバー及び協賛メンバーの紹介があった。

続いて、議題 2 として両側を代表し、環境省 環境再生・資源循環局 廃棄物適正処理推進課 浄化槽推進室長の沼田 正樹 氏と、ジャル・シャクティ省国家河川保全局(National River Conservation Directorate, Ministry of Jal Shakti, 以下、NRCD)の Joint Secretary (次官補1) である Shri Pradeep Kumar Agarwal (シュリ プレディープ クマール アガールワル)氏より基調演説があった。なお、議題に記載はないが、インド側からの基調演説では、ジャル・シャクティ省の設立経緯や役割、組織の紹介が行われた。このインド側を紹介する発表資料については資料編 6.3.1. に示す。

議題3では、共同作業計画書及び第1回セミナープログラムについて審議が行われた。共同作業計

¹ インド側出席者の役職の日本語訳については「文部科学省スポーツ庁の在り方に関する調査研究事業(平成24年度)第6章インド(https://www.mext.go.jp/a_menu/sports/chousa/detail/1333391.htm)」の図表-6-9(インド行政職(IAS)職員 役職の類型)を参考にした。

画書についてはインド側より、Annexure II のパイロットプロジェクトのプロモーターについて「National Mission for Clean Ganga, Ministry of Jal Shakti (Department of Water Resources, River Development & Ganga Rejuvenation) Government of India」となっているところを、National Mission for Clean Ganga(国家ガンジス川浄化ミッション)も包含する「Ministry of Jal Shakti, Government of India」のみの記載にしてはどうか、との提案があり、両側がこの変更に合意した。また、セミナーのプログラムについても 2023 年 12 月 19 日に開催することを含め両側が合意した(セミナープログラムについては資料編 6.4. に記載)。

議題 4 として、両側の協賛メンバーも自社の取り組みや自社製品・技術に関し紹介する発表を行った。しかし、インド側協賛メンバーである Arvind Envisol Ltd.はインターネット回線が不安定であるため発表をすることが出来なかった。同じく日本側協賛メンバーである株式会社ハウステック及び株式会社日吉についても、日程が合わなかったために第1回会議体会合を欠席し、発表は行っていない。議題4に係る両側の協賛メンバーによる発表資料については、資料編6.3.2.~6.3.7.に示す。

2.3.2. 有識者への謝金の支払い・同時通訳者の傭上

会議開催に当たっては、日本語・英語の同時通訳者を傭上し、前述の「2.1. 会議体構成メンバー表及び共同作業計画書の作成」において決定した日本側会議体メンバーのうち有識者に対し、請負者より謝金(1人1日につき17,700円)及び国家公務員等の旅費に関する法律に基づく旅費(6~3級相当)を支給した。

2.3.3. 第1回会議体会合議事要旨

第1回会議体会合開催後、受託者で議事要旨案を作成しインド側とメールで協議を重ね議事内容の確認を行った。最終版の第1回会議体会合議事要旨について以下に示す。

なお、資料編 6.2. 第1回会議体会合プログラムではインド側会議体メンバーの一人として在日本インド国大使館の Ms. Madhuri Gaddam(マドゥリ ガダム)氏が記載されているが、異動により後任の Mr. Shishir Kothari(シシル コタリ)氏が出席した。





Minutes of the First Meeting of the Management Council under India-Japan Memorandum of Cooperation (MoC)

Date	29 th November, 2023					
Time	12:30-14:30 in Indian time					
	16:00-18:00 in Japanese time					
Agenda	Introduction on Both sides of Management Council members cum Approval of Associate members Key note Speeches (from both sides) Approve the Joint Working Program and the 1st Seminar program Presentation from the Associate members of both the sides					
Venue of	Conference Room, NMCG and Video Conference					
Indian side						
Venue of	Meeting room, Japan Education Center of Environmental Sanitation					
Japanese side	(JECES)					

A Memorandum of Cooperation (MoC) was signed on 19th March, 2022 between Ministry of the Environment, Government of Japan and The Ministry of Jal Shakti Government of India, in the areas of 'De-centralized Domestic Wastewater Management and Effective Reuse of Treated Wastewater'. This cooperation seeks to provide solutions to various water related issues, encourage and facilitate cooperation in the areas of mutual interest, through exchanging information and expertise, organizing seminars, conferences and meetings, and capacity building through trainings and workshops.

The First Meeting of the Management Council (MCM) was organized on 29th November 2023. This meeting was organized under the Chairmanship of Joint Secretary, National River Conservation Directorate, Ministry of Jal Shakti, Government of India, from the Indian side and Director of Office for Promotion of Johkasou, Waste Management Division, Environmental Regeneration and Material Cycles Bureau, Ministry of the Environment, Government of Japan, from the Japanese side.

A total of 29 participants attended the meeting, out of which 14 attended in person from the Conference Hall at National Mission for Clean Ganga (NMCG) and the Meeting room, Japan Education Center of Environmental Sanitation (JECES) (Please refer Annexure-I for the name of participants) and 15 participants attended through video conference (Please refer Annexure-II for the name of participants). The participants included Permanent Members and Associate Members from both India and Japan side. The meeting was coordinated by National Mission for Clean Ganga from India side, and by Office for Promotion of Johkasou, Waste Management Division, Environmental Regeneration and Material Cycles Bureau, Ministry of the Environment, Government of Japan, from the

Japanese side. The proceedings of the meeting are as under:

- 1. Shri Dheeraj Joshi, Deputy Secretary, NMCG and Mr. Ryoma Sato, Section Chief, Office for Promotion of Johkasou welcomed the members to the session and introduced the agenda of the First Meeting of the Management Council.
- Keynote address was delivered by Shri Pradeep Kumar Agarwal, Joint Secretary, National River Conservation Directorate, Ministry of Jal Shakti, Government of India, and Mr. Masaki Numata, Director, Office for Promotion of Johkasou, Waste Management Division, Ministry of the Environment, Government of Japan.
- 3. Shri Agarwal introduced the Key Government Schemes in Indian water sector. He also introduced core activities of the Ministry of Jal Shakti, and major departments of the government dealing with water under its aegis. Further, he introduced the Namami Gange Projects that the Ministry of Jal Shakti is working on.
- 4. Ms. Thi Mai Hoang, Senior Environment Expert Office for Promotion of Johkasou, Waste Management Division, Environmental Regeneration and Material Cycles Bureau, Ministry of the Environment Government of Japan, explained the Joint Working Program and the draft Seminar program.

Both Shri Agarwal and Mr. Numata expressed the importance of De- centralized Domestic Wastewater Management and the role of technology in addressing the same.

- 5. After deliberations, both sides agreed to the following-
- (i) Draft Joint Working Program was accepted by both sides with few amendments as below:

Name of the promoter of pilot projects in Annexure II of the draft Joint Working Program was 'National Mission for Clean Ganga, Ministry of Jal Shakti (Department of Water Resources, River Development & Ganga Rejuvenation) Government of India', which is amended to 'Ministry of Jal Shakti, Government of India'

- (ii) To proceed with preparations to hold the 1st Seminar on 19th December, 2023 after this first MCM.
- (iii) To discuss again on holding the 2nd MCM after the 1st seminar is held on 19th December, 2023, if necessary.
- (iv) Management Council members and Associate Members nominated from the Indian as well as Japanese side (Names of the Associate Members are mentioned at Annexure-III).

- 6. A total of 7 Associate Members were present- 4 from India side and 3 from Japanese side. Brief presentations were made by following 5 Associate Members on the technologies and the work being done in De-centralized Domestic Wastewater Management and effective reuse of treated wastewater.:
 - a. Sintex BAPL Ltd.
 - b. Daiki Axis India Pvt. Ltd.
 - c. Kubota Johkasou System Co., Ltd.
 - d. FujiClean Co., Ltd.
 - e. Daiki Axis Co., Ltd.

Arvind Envisol Ltd., another Associate member of the Indian side, was unable to make presentation due to the internet environment. In addition, Housetec Inc. and Hiyoshi Corporation, the other Associate members of Japanese side were absent from this 1st Management Council Meeting (MCM) because of their schedule issue.

7. The meeting was concluded with a vote of thanks by Shri Dheeraj Joshi, Deputy Secretary, National Mission for Clean Ganga, Ministry of Jal Shakti, and by Mr. Ryoma Sato, Section Chief, Office for Promotion of Johkasou, Waste Management Division, Ministry of the Environment, Government of Japan.

Annexure-I

List of participants who attended the meeting in person at the conference hall, NMCG

S.No.	Name	Designation			
1.	Shri Pradeep Kumar Agarwal	Joint Secretary, National River Conservation Directorate, Government of India			
2.	Shri Dheeraj Joshi	Deputy Secretary, National Mission for Clear Ganga			
3.	Dr. Pravin Kumar	Director (Technical), National Mission for Clean Ganga			
4.	Ms. Diva Pandey	Institutional Associate, National Mission for Clean Ganga			
5.	Mr. Vishal Garg	Institutional Associate, National Mission for Clean Ganga			
6.	Mr. Ashwini Dubey	Support Architect, RFD and URMP, National Mission for Clean Ganga			
7.	Mr. Kamal Tiwari	CEO, Daiki Axis India Pvt. Ltd. India			
8.	Mr. Rio Waza	Managing Director, Daiki Axis India Pvt. Ltd., Japan			

List of participants who attended the meeting in person at the Meeting room, Japan Education Center of Environmental Sanitation (JECES)

S.No.	Name	Designation			
1.	Mr. Ryoma Sato	Section Chief, Office for Promotion of Johkasou, Waste Management Division, Ministry of the Environment			
2.	Dr. Kiyoshi Kawamura	Former Professor, Saitama University			
3.	Dr. Yoshitaka Ebie	Manager, Planning Division (International Coordination Office), National Institute for Environmental Studies (NIES)			
4.	Dr. Shinhi Kumokawa	Director, Center for International Cooperation of Johkasou System Japan Education Center of Environmental Sanitation (JECES)			
5.	Dr. Yurie Shirakawa	Senior Researcher, Center for International Cooperation of Johkasou System Japan Education Center of Environmental Sanitation (JECES)			
6.	Ms. Ayako Suzuki	Researcher, Center for International Cooperation of Johkasou System Japan Education Center of Environmental Sanitation (JECES)			

Annexure-II

List of participants who attended the meeting through video conference

S. No		Designation
1.	Shri Anup Kumar Srivastava	Executive Director (Technical)
2.	Mr. Masaki Numata	Director, Office for Promotion of Johkasou,
		Waste Management Division, Ministry of the
		Environment
3.	Ms. Thi Mai Hoang	Senior Environment Expert of Office for
		Promotion of Johkasou, Waste Management
		Division, Ministry of the Environment
4.	Mr. Ikuro Kasuga	Professor, Research Center for Advanced
		Science and Technology, The University of
		Tokyo
5.	Dr. Mihoko Nagai	First Secretary, Embassy of Japan in India
6.	Prof. A. A. Kazmi	Professor, Indian Institute of Technology
		Roorkee
7.	Dr. Ram Avtar	Associate Professor/Director, Hokkaido
		University/Global Land Programme
8.	Mr. Shishir Kothari	First Secretary, Political, Press &Information,
		Thematic Cooperation, Head of Chancery,
		Embassy of India in Tokyo
9.	Mr. Shubham Tiwari	Co-lead Institutional Associate
10.	Mr. Amit Shah	Head Global, Arvind Envisol Ltd.
11.	Mr. Naveena Nand Upadhyay	Deputy General Manager-R&D, Design, Sintex
		BAPL Ltd
12.	Mr. Yoshito Kitai	Deputy Manager, Kubota Johkasou System
		Co., Ltd
13.	Mr. Yosuke Tabata	Executive Officer, Overseas Business Group,
		FujiClean Co., Ltd
14.	Mr. Kazuo Saeki	Manager, Daiki Axis Co., Ltd

Annexure-III

List of Associate Members (Temporary members) nominated for both sides is presented in the tables below.

Indian side of Associate Members (Temporary members)

No	Designation	Organization/ Institution	Name
1	Head Global	Arvind Envisol Ltd.	Mr. Amit Shah
2	Deputy General	Sintex BAPL Ltd.	Mr. Naveena Nand
	Manager - R&D,		Upadhyay
	Design		
3	CEO	Daiki Axis India Pvt. Ltd.	Mr. Kamal Tiwari
4	Associate	Hokkaido University/	Dr. Ram Avtar
	Professor/Director	Global and Programme	

Japanese side of Associate Members (Temporary members)

No	Designation	Organization/Institution	Name
1	Manager	Daiki Axis Co., Ltd.	Mr. Kazuo Saeki, Ph.D.
2	Executive Officer, Overseas Business Group	FujiClean Co., Ltd	Mr. Yosuke Tabata, Ph. D.
3	Manager	Housetec Inc.	Mr. Koji Tsukamoto
4	Deputy Manager	Kubota Johkasou System Co., Ltd.	Mr. Yoshito Kitai
5	Chief, Research and Development Planning Office	Hiyoshi Corporation	Mr. Kazuhiko Matsui



インド側会場



日本側会場



Shri Pradeep Kumar Agarwal (シュリ プレディープ クマール アガールワル氏) Joint Secretary, NRCD



沼田 正樹 氏 環境省 環境再生・資源循環局 廃棄物適正 処理推進課 浄化槽推進室 室長



Shri Dheeraj Joshi (シュリ ディーラジュ ジョシ 氏) Deputy Secretary, NMCG



佐藤 亮真 氏 環境省 環境再生・資源循環局 廃棄物適正 処理推進課 浄化槽推進室 指導普及係長



ホワン ティー マイ 氏 環境省 環境再生・資源循環局 廃棄物適正 処理推進課 浄化槽推進室 環境専門調査員



Mr. Naveena Nand Upadhyay (ナヴィーナ ナンヂュ ウッパードゥヤイ 氏) シンテックス BAPL 社 研究開発設計部 部長代理



Mr. Kamal Tiwari (カマル ティワリ 氏) 株式会社ダイキアクシス インド法人 CEO



北井 良人 氏 クボタ浄化槽システム株式会社 四国営業所 営業技術担当



田畑 洋輔 氏 フジクリーン工業株式会社 海外事業部 執行役員



佐伯 和男 氏 株式会社ダイキアクシス 海外事業統括本部 海外営業統括部 海外営業部 海外営業推進課 課長

図 3 第1回会議体会合発表者

第3章 セミナーの開催

3.1. セミナーの詳細プログラムの作成

第1回会議体会合で承認されたセミナーのプログラムに沿って発表者を選定し、開催日時、開催方法、司会者について環境省担当官及びインド側と協議の上、セミナーの詳細プログラムを作成した。 第1回会議体会合で既に提供された情報と重複が無いよう、且つ、日本で浄化槽がどのように普及して利用されているのかをインド側に効果的に伝えることが出来るよう、プログラムを作成した。 完成したプログラムを資料編 6.4. に示す。

3.2. セミナーの開催

3.2.1. 開催概要

2023年12月19日にセミナーをオンラインで開催した。開催概要を表5に示す。

表 5 セミナーの開催概要

日	時	2023年12月19日 日本時間15:00~17:00 (インド時間11:30~13:30)			
会	場	インド側: NMCG 会議室			
		日本側:日本環境整備教育センター 4F 会議室			
		Zoom (Web 会議システム) の Webinar を使用しインド側会場と日本側会場を接続した			
内	容	1. Opening remarks from both side(両側からの開催挨拶)			
		2. Presentation (発表)			
		3. Closing (閉会)			

はじめに両側を代表し環境省環境再生・資源循環局 廃棄物適正処理推進課 浄化槽推進室長の沼田 正樹氏と、NMCGの Director General (総局長1)である Shri Asok Kumar (シュリアショク クマ ール)氏より開会挨拶があった。

続いてインド側からは1件、日本側からは6件の情報提供及び発表があった。

インド側からは、NMCGの Deputy Secretary (課長)である Shri Dheeraj Joshi (シュリ ディーラジュ ジョシ)氏から、インドにおける生活排水処理状況について発表があった。インド側がガンジス川流域で展開する環境改善事業における実施内容(下水道施設の整備、河川敷の整備、固形廃棄物の処理、など)や、地方州における生活排水処理施設の整備状況、リアルタイムでの水質モニタリングシステム、水質改善状況の紹介が行われた。また、現在のインド国内の汚水管理状況を向上させるため、浄化槽などの分散型汚水管理も積極的に推進していく計画であるとの紹介も行われた。

日本側からは、環境省 資源循環局 廃棄物適正処理推進課 浄化槽推進室の佐藤 亮真 氏より、日本の生活排水処理の現状と集中・分散処理システムの管理について、そして、浄化槽法をはじめとする日本における生活排水の分散管理に関する法制度に関して発表があった。

続いて日本環境整備教育センターの雲川 新泌 氏からは、日本で浄化槽の保守点検、清掃、検査が どのように行われているか、また、資格者制度と汚泥管理について紹介があった。

また、日本側協賛メンバーであるフジクリーン工業株式会社 海外事業部 執行役員の田畑 洋輔 氏からは、分散型汚水処理施設に関する性能評価試験制度の必要性について、株式会社クボタ浄化槽シ

ステムの担当部長である北井 良人 氏からは、日本の浄化槽の人員算定基準について、株式会社ダイキアクシスの課長である佐伯 和男 氏からは、浄化槽の国内外における施工事例について、それぞれ発表があった。

その後、発表内容に関して質疑応答が行われ、両側から積極的に質問やコメントがなされた。発表 資料については資料編 6.5. に、質疑応答の記録については資料編に 6.6. に示す。なお、セミナー開催 後に日本側会議体メンバーから追加で挙げられた質問については資料編 6.7. に整理している。


セミナーの最後に、環境省 環境再生・資源循環局 廃棄物適正処理推進課 浄化槽推進室 指導普及 係長の佐藤亮真氏と、NRCD の Director (局長 1) である Mr. Nelapatla Ashok Babu (ネラパトラ アショク バブ) 氏よりそれぞれ閉会挨拶があった。



インド側会場の様子



日本側会場の様子



羽田 正樹 氏 環境省 環境再生・資源循環局 廃棄物適正処理 推進課 浄化槽推進室 室長



Shri Asok Kumar (シュリ アショク クマール 氏) NMCG, Director General



Shri Dheeraj Joshi (シュリ ディーラジュ ジョシ 氏) Deputy Secretary, NMCG



佐藤 亮真 氏 環境省 環境再生・資源循環局 廃棄物適正処理 推進課 浄化槽推進室 指導普及係長



Mr. Nelapatla Ashok Babu (ネラパトラ アショク バブ 氏) Director, NRCD



雲川 新泌 氏 公益財団法人日本環境整備教育センター 浄化槽システム国際協力センターリーダー



田畑 洋輔 氏 執行役員



北井 良人 氏 フジクリーン工業株式会社 海外事業部 クボタ浄化槽システム株式会社 四国営業所 営業技術担当



佐伯 和男 氏 株式会社ダイキアクシス 海外事業統括本部海外営業統括部 海外営業部 海外営業推進課 課長

図 4 第1回セミナー発表者

3.2.2. 有識者への謝金の支払い・同時通訳者の傭上

請負者はセミナーの開催に当たって日本語・英語の同時通訳者を傭上し、前述の「2.1. 会議体構成メンバー表及び共同作業計画書の作成」において決定した日本側会議体メンバーのうち有識者に対して、請負者より謝金(1人1日につき17,700円)及び国家公務員等の旅費に関する法律に基づく旅費(6~3級相当)を支給した。

3.2.3. セミナーにおける質疑応答

セミナー開催後、セミナーの中で行われた質疑応答と、後日、日本側会議体メンバーから挙げられた追加質問について一覧的に整理した。資料編 6.6. 及び 6.7. に示す。なお、インド側の回答は報告書作成時点で受領できていない。

第4章 来期の共同作業に関する調整

2022 年 3 月 19 日に締結された日本側とインド側との間の分散型生活排水管理分野における協力覚書 (MOC) に依れば、その活動期間は 2 年間とされており、2024 年 3 月に期限を迎えるが、MOC の第 10 項には両側の同意により MOC を延長することが出来るとされている。

そこで、インド側に MOC の延長の意思確認を行ったところ、2024 年 2 月 7 日にインド側担当官から連絡があり、2 年間の MOC 延長(2026 年 3 月 19 日まで)についてインド側大臣の承認が得られた旨の連絡があった。

なお、延長後の MOC に基づく活動はインド側が主体となり進めていくことになっており、MOC 延長の意思を確認する際、併せて MOC 延長後の活動計画等についてインド側に提供を求め、2024 年 3 月 6 日に資料を受領した。

第5章 環境省担当官との打合せ

5.1. 第1回打合せ

日時	2023年8月16日 (水) 13:40~14:45	
場所	環境省 23階会議室	
出席者	環境省浄化槽推進室:佐藤係長、ホワン様	
	在インド国日本大使館:永井様(オンライン参加)	
	日本環境整備教育センター(JECES):雲川、白川、鈴木	

1. 本年度業務の実施方針の確認

環境省担当官より提供があったキックオフミーティング資料と受託者が用意した業務実施計画書 (案)及び業務工程表に沿って令和5年度業務の実施方針を確認した。

1.1 協力覚書 (MOC) についての留意事項

- ▶ 環境省担当官より、本 MOC において日本側が提供できるものは日本の浄化槽に係るものの みに留まることをインド側にも確認済みである旨の報告を受けた。
- ➤ 本 MOC の有効期限は2年間であり、延長に関しては本セミナー開催後に決定となる可能性が高い。セミナー終了後にJECESよりインド側に確認し、要望があれば受けることを共有した。確認する際、業務遂行における主体はインド側であると明確に伝えるようにとの環境省からの指示があった。今後のセミナー等の発表データを協議する際、日本の浄化槽以外の分散型排水処理設備は対象外であることを留意すること。

1.2 第1回会議体会合及びセミナーについて

- ▶ 開催時期:会議体会合は9月に開催するのが理想だが、どうしても難しい場合にあっては10月になることも差し支えない。インド側の都合も考慮して年内にセミナーまで終えるよう調整することを共有した。
- ▶ 開催形式: JECES より、第1回会議体会合及びセミナーへの協賛メンバーの参加について、可能な限り対面で参加するようにとあるが難しい場合はウェブでの参加でもよいかと確認し、環境省より了承を得た。
- ▶ また、環境省担当官より、会議体会合及びセミナーでは、日本側だけでなくインド側協賛メンバーから発表していただくことも検討するよう提案を受けた。ただし、インド側に知見をもった会社がない場合には日本側のみの発表でも差し支えない。加えて、会議体会合では、セミナープログラム案や共同作業計画書の内容について議論するというより、承認を得ることを目的とし、第1回会議体会合の開催前に両側で内容を十分つめておくよう指示があった。
- ➤ JECES はセミナーのプログラム案について、環境省担当官からの指示に基づき主に以下の点を修正する;①ビデオの放映時間は12分程度を見込む、②協賛メンバーによる発表件数が多くなる場合は全体の時間を調整する、③両側代表の基調講演の時間を短縮する。
- ▶ 永井様より、第1回会議体会合及びセミナーの円滑な開催に向け、以下3点を同時にインド側に照会したほうが良いとの助言があった;①第1回会議体会合の次第案の確認、②第1回会議体会合及びセミナー開催に向けた日程調整、③日本側協賛メンバーは5社になった旨の伝達。

1.3 会議体構成メンバーについて

- ▶ 環境省担当官より、春日教授はインドもしくは分散型汚水処理に関する実績及び研究をされているかという質問を受けた。JECESから、インドについては不明であるものの、途上国の排水処理に関して幅広くコメントを頂けるであろうことを回答した。
- ▶ インド側メンバー表に関して、S.No6 の IIT・Roorkee はインドにおける分散型汚水処理の第

1 人者である Kazmi 教授、S.No5 はチャーリー教授である可能性が高い旨を JECES より報告した。

1.4 協賛メンバーについて

- 日本側の協賛メンバー
- ▶ 日本側の協賛メンバーとして、昨年浄化槽システム協会が協会メンバーに参加意向を確認していただいた際、ダイキアクシス、フジクリーン工業、ハウステックとニッコー4社の意向が確認出来たが、先月再度確認していただいたところ、ダイキアクシス、フジクリーン工業、ハウステックとクボタ4社は参加意向があり、また、JECESが声をかけた日吉を入れて5社となった。JECESは今後の業務を推進する際は、協賛メンバー内にて優劣はつけず、また、5社全てから発表いただけるとの回答を得られた場合は、その方向でプログラムの時間等を調整すること。
- ➤ 永井様より、ダイキアクシス社は MOC を締結する発端となった企業であるが、他の協賛メンバーと同等の位置づけで特別な配慮は必要ないとの提案があり、JECES も同意した。ただし、特別な配慮が必要ない点は同意したうえで、同社はインド側の状況に精通している企業であることから、意見を求めるなど同社の知見を基に協力いただく場合は問題ないのでは、と環境省担当官より言及があった。
- インド側の協賛メンバー
- ➤ 在インド国日本大使館の永井様より、人事異動によって新たに Mathuria 課長の部下となられた担当の Dubey 様から、インド側の協賛メンバーとしてインドの民間企業の中から分散型排水処理に知見のある企業を選定したいが情報がないため難しい、もし日本側に知見があればインド側の企業を選定していただきたい、という趣旨のメールが送られてきた旨、情報共有があった。2023 年 3 月の時点で日本と同数の民間企業を参加させたい、という話を Mathuria 課長がされていた旨も共有があった。これに対し JECES は、インド企業に関して知見がないと回答した
- ➤ JECES は Kazmi 教授にインド側協賛メンバーとなりうる分散型汚水処理関連企業の紹介を 依頼することになった。

1.5 共同作業計画書の内容について

- ➤ 環境省担当官から永井様に、共同作業計画書の 3. Forms of Cooperation の Note for Indian side は最新版では削除されているが、理由があればご教示願いたいとの照会があった。永井様から、Note は注釈のため最終的に削除されるものという認識にて削除したと回答があった。
- ➤ 永井様から、共同作業計画書の「4.Cooperating Partner」でインド側にも事務局を設置し、「5.Beneficiaries」で SDG6.3 に寄与する、といったように内容を変更せず修辞上の修正を日本側で行い、インド側に確認を求めているが返答がない状況である、との共有があった。
- ➤ 共同作業計画書について環境省担当官は最終確認のうえ JECES と共有し、JECES よりインド側に改めて確認を依頼すること。また、永井様より、インド側から提供された初稿版をJECES と共有いただけることとなった。

1.6 インド側との連絡について

- ➤ 永井様より、Tiwari 様は秘書部門の方であり、オンライン会議の設定や日程調整等のロジを担当されていると思われる、との情報共有があった。人事異動の関係で、担当である Dubey 様は本件の詳細を把握していないため、メールの送信時は Tiwari 様含め局長以下全員を宛先に入れること、特に重要な事項の場合は Mathuria 課長に電話したほうが良いとの助言も頂戴した。
- ➤ また、永井様より、インドは反応が遅いため、メールは1度ではなく複数回送付し、かつ電話でフォローアップすることが必要である旨、助言を頂戴した。後日、永井様から Mathuria 課長の名刺をデータで共有いただくことになった(8月17日に永井様から環境省経由でJECESに情報共有済み)。

2. 業務ロジ

- ➤ 再委任等承諾申請書は予定がないため提出が不要。契約書は JECES から環境省の担当部門 へ提出し、担当部門から浄化槽推進室に共有されることと承知しており、浄化槽推進室へ直接 契約書の写しを提出することは不要。情報セキュリティ対策資料は他業務同様に印刷物で準備 のうえ、対面にて提出すること。
- ▶ JECES は本打合せを踏まえて業務実施計画書を修正し、再度提出すること。
- ➤ JECES は業務工程表をより詳細な作業項目を抽出するよう修正し、再度提出すること。

3.その他

特になし

5.2. 第2回打合せ

日時	2023年11月27日(月)13:30~
場所	環境省 23 階会議室
出席者	環境省浄化槽推進室:沼田室長、佐藤係長、ホワン様
	日本環境整備教育センター(JECES):雲川、白川、鈴木

1.第1回会議体会合プログラム

- ▶ JECESより第1回会議体会合のプログラムについて説明を行った。
- ➤ 環境省担当官より、インド側は所定の時間が延長する前提でプログラムを約1時間30分で組んでいるとのことだが、Agendaのどこで延長が発生するとインド側が考えているのか、質問があった。JECESより、どの部分が延長するのかはインド側に確認していないので分からないが、インドと会議をする際の特徴として、全体的に発言内容が冗長的で長くなる傾向があることを報告した。
- ➤ 環境省担当官より、会議の議事進行役は誰が行うのか質問があった。JECES より、日本側で会議を進行させて欲しいと伝えたが、インド側も司会者を立てたいとの要望があり担当者のMr. Shubham Tiwari 氏がインド側の司会を務める予定であることを回答した。
- ▶ 環境省担当官より、最近、インド側が会議開催に向けて積極的な姿勢を見せるようになったが、第2回会議体会合の開催をインド側は前向きに検討しているということか、との照会があった。JECESより、インド側は8人目の会議体メンバーの追加について結局断念していることもあり、現状ではよくわからないと回答した。環境省より、セミナーを開催した後に正式にインド側に確認することになると思うが、第1回会議体会合の流れ次第では、その場で第2回会議体会合の開催についてお尋ねしても良いかと思う、とのコメントがあった。インド側が、12月中に第1回会議体会合とセミナーを終わらせ、次年度のパイロットプロジェクトや第2回会議体会合を早めに計画したいといという考えを持っている可能性について言及があった。
 - ➤ JECES より、インド側の組織改編によって Mr. Shri Davendra Pratap Mathuria 課長が異動し、Mr. Shri Anup Kumar Srivastava が後任となり、会議体メンバーにもノミネートされていることを報告した。
 - ➤ 環境省担当官より、パイロットプロジェクトの時期や規模、実施地域等、具体的情報を持っているか照会があった。JECES より、過去に前任の環境省担当官から伺った話によると、Jal Shakti 省で独自に予算を確保して浄化槽を面的に整備したいとのことであったが、最新情報を得ていないので現状の詳細は承知していないことを回答した。
 - ▶ 環境省担当官より、第 1 回会議体会合を欠席する日本側メンバーはいるのか質問があった。

JECES より、会議体メンバー3名とも出席すること、協賛メンバーのうちハウステックと日吉は欠席することを報告した。JECES は、在インド日本大使館の永井様にも第1回会議体会合に出席いただけるか確認しておくこと。

- ▶ 環境省担当官より、第 1 回会議体会合のプログラム内に誤字があるので修正しておくこと、 また永井様の Designation として Fist Secretary 記載しておくよう指示があった。
- ➤ 環境省担当官より、インド側協賛メンバーの Arvind Envisol Ltd. についてどういう会社か 確認しておくよう指示があった。JECES より、インターネットで調べてみるが、第1回会議 体会合の際に先方から発表資料をもらうことで情報が得られる可能性があることを回答した。
- ▶ 環境省担当官より、協賛メンバーの紹介が長くならないようインド側に事前に申し入れておくよう指示があった。
- ➤ 環境省担当官より、第 1 回会議体会合の冒頭で佐藤係長が日本側会議体メンバーを紹介する際の紹介文は JECES が提案書に記載した内容で問題ないか照会があり、JECES より、問題ない旨回答した。

2. セミナープログラム

- ▶ 環境省担当官より、第 1 回会議体会合でこのセミナーのプログラムが確定するのではないのか、との質問があった。JECES より、セミナーのプログラム案はインド側に共有しているが、インド側からは未だレスポンスがないので第 1 回会議体会合で確定できるかは見通せないことを回答した。
- ▶ 環境省担当官より、セミナーの発表者にも発表を依頼しなければならないので、なるべくなら第1回会議体会合で確定させること、もし第1回会議体会合で確定できなかった場合は、インド側と調整し11月中にプログラムを確定させるよう指示があった。
- ▶ 会議体メンバーの出欠について確認し、改めて環境省に報告する。

5.3. 第3回打合せ

日時	2023年12月6日(水)10:50~11:30
場所	環境省 23 階会議室
出席者	環境省浄化槽推進室:沼田室長、佐藤係長、ホワン様
	日本環境整備教育センター(JECES):雲川、武田、白川、鈴木

1. セミナー開催にあたって

(1) プログラムに関して

- ➤ JECES より、プログラムに記載されている日本側の協賛メンバーの発表者全員から発表 に係る了承を頂いている旨を報告した。
- ➤ JECES より環境省が担当する 2 つのテーマの発表者について尋ねたところ、環境省担当 官が 2 つのテーマ両方について発表すると回答があった。また、環境省担当官より、2 つのテーマを連続して発表するため、10 分及び 8 分の合計 18 分の持ち時間を合計 15 分に まとめるが、プログラムは変更しなくても良い旨、指示があった。

加えて環境省担当官より、浄化槽法に関する内容である2つ目のテーマについてはより重点的に解説を行ったほうが良いため、1つ目を7分とする予定であるとの共有があった。

➤ JECES より、環境省の閉会挨拶は誰が実施するのか質問し、環境省担当官より佐藤係長が行うと回答があった。

- ➤ 環境省担当官より、技術面に関する質問が多く出ることが想定されるため、環境省担当官による発表時間が3分短縮されることから、2回目の質疑応答を16分から3分延ばして19分としたほうが良いのではと提案があり、JECESは同意した。
- ➤ 環境省担当官より、現状のプログラムでは時間に余裕がないため、発表準備等で予定の時間から遅延するのを想定し、1回目の質疑応答の後に休憩時間を5分間設け、遅延した場合は休憩を挟まずに進行するのはどうかと提案を受け、JECESは同意した。
- ▶ 当日の司会進行担当は白川氏の予定。

(2) Zoom の事前登録に関して

- ➤環境省担当官より、セミナーは事前登録制か照会があり、JECES より、事前登録制にしていた別業務で開催した第 11 回ワークショップでは、メールアドレスの入力ミス等で参加用の Zoom アドレスが届かないとの連絡を複数名の参加者から受けたため、事前登録制にすると円滑に参加が出来ないのではないかと考え、セミナーは事前登録制にしていないと回答した。
- ▶環境省担当官より、Zoomのアドレスは公開するのか照会があり、JECESより HP に掲載して公開予定であることを回答した。環境省担当官より、Zoom会議参加用 URL アドレスを知っていれば誰でも参加可能な状況は避けたほうが良い、参加者の属性等の情報も把握できないということか、と質問があり、JECESはご認識の通りであると回答した。
- ➤環境省担当官より、インド側で参加者の情報を取りまとめてもらえるのであれば事前登録制にしたり Zoom アドレスを公開したりする必要はない、ジャル・シャクティ省にのみ Zoom アドレスを送付し、ジャル・シャクティ省からインド側の参加者に配布してもらえばいいのではと提案を受け、JECES は了承した。

併せて、属性情報を記載するフォーマットを JECES が作成しインド側に送付するよう環境省担当官より指示があり、JECES は了承した。

(3) セミナーの案内に関して

ジャル・シャクティ省以外にも本セミナーの案内をするかは環境省担当官が改めて検討し、 追って JECES に指示することとなった。

(4)参加後のアンケートに関して

環境省担当官より、セミナーの評価と今後の参考のため、参加後の感想を求めるアンケートを作成するよう指示があり、JECES は了承した。アンケート機能を使うため、Webinar の形式で実施する予定。

2. その他

JECES より、セミナー開催前に打合せ(第 4 回業務打合せ)を行いたい旨を伝え、環境 省担当官は了承した。追って開催に向けて日程調整を行うことに合意した。

5.4. 第4回打合せ

日時	2023年12月18日(月)15:00~16:00
場所	環境省 23 階会議室
出席者	環境省浄化槽推進室:沼田室長、佐藤係長、ホワン様
日本環境整備教育センター(JECES):雲川、白川、鈴木	

(1) 第1回会議体会合議事要旨

▶ 第1回会議体会合議事録にインド側会議体メンバーとして記録されていた在日本インド大使館の Mr. Shishir Kothari について、正式な会議体メンバーであるか、また、なぜ変更になっ

たのか、JECES はインド側に確認すること。併せて、JECES は、第 1 回会議体会合の録音を聞き返して確認すること。

➤ JECES は、共同作業計画書に記載があるパイロットプロジェクトの実施主体について、第1回会議体会合議事録においてインド側が記載した通りに修正のうえ、インド側に確認を求めること。

(2) セミナー

- ➤ JECES より 12 月 18 日時点で受領している発表資料について共有した。環境省担当官より、スライド番号が無い資料については JECES で番号を付したうえでウェブサイトに掲載すること。
- ▶ 日英同時通訳の質を高めるため、発表者からはなるべく読み原稿を受領すること。
- ▶ 12 月 19 日のセミナーでは発表者に時間厳守の旨周知を図り、司会を担当する JECES は、 万一割り当てられた時間を超過した発表者がいた場合は強制的に次の発表に移行する。
- ▶ QA セッションについても同様に時間厳守の徹底を基本とするが、メーカー各社の発表の後に設けられた質疑応答セッションは多少延長しても問題ない。
- ➤ インド側から提供された出席者リストの人数が少なかったことから、Webinar 参加者向けの アンケートは実施せず、セミナー終了後にインド側、日本側が双方で質問やコメントを QA リ ストに取りまとめて両者がそれぞれ回答を作成すること。
- ➤ 第1回会議体会合の際はインド側で音声が聞こえないという訴えがあったことから、今般のセミナー開催に当たっては、インド側に言語選択ボタンの操作をセミナーの冒頭でアナウンスすること。Zoom 会議のホストである JECES は、Webinar 参加者全員のステイタスをパネリストに変更し、発言及び画面の共有ができるようにすること。
- ▶ 万一、セミナーの中でインド側から第2回会議体会合の開催について言及があり何らか日本側の発言を促すような場面になった際は、佐藤係長に対応いただく。

(3) その他

▶ 2024 年 1 月 10 日から 21 日にかけて海外出張(ADBI 業務のインド現地調査)のため、 JECES はメールへの返信等レスポンスが遅くなることを共有した。

第6章 資料編

6.1. 最終版の共同作業計画書

JOINT WORKING PROGRAM

The Ministry of the Environment of Japan and the Ministry of Jal Shakti of the Republic of India (hereinafter referred to as individually as a "Side" and collectively as "Both Sides") hereby describe this Joint Working Program in accordance with the "MEMORANDUM OF COOPERATION BETWEEN THE MINISTRY OF THE ENVIRONMENT OF JAPAN AND THE MINISTRY OF JAL SHAKTI OF THE REPUBLIC OF INDIA IN THE AREAS OF DECENTRALIZED DOMESTIC WASTEWATER MANAGEMENT" (hereinafter referred to as "the signed MOC"), which was signed on March 19, 2022.

This Joint Working Program describes the details for the implementation of the joint work which is carried out based on this Joint Working Program (hereinafter referred to as "Joint Work") and, if approved by the first annual meeting of the Management Council, a detailed document with a specific and detailed program table, etc. mentioned in the signed MOC (hereinafter referred to as "Detailed Document") will be prepared. After Both Sides agree to adopt a Detailed Document submitted to Management Council, the first Joint Work will be implemented based on the adopted Detailed Document. If Both Sides have the wish to initiate the second Joint Work, Both Sides will discuss and adopt an additional Detailed Document. Detailed Documents will be treated as Appendix to this Joint Working Program.

1. Objectives

Based on the signed MOC, Both Sides will pursue the collaboration by utilizing Japanese Johkasou Technology for the purpose of improving Indian water environment in the categories such as operation, maintenance, desludging and inspection, as well as the registration and licensing system for the above-mentioned categories, the performance testing evaluation system for Johkasou, and treatment and disposal of Johkasou sludge. The collaboration also includes information sharing on technologies and business models by Japanese Johkasou Manufactures, while bearing in mind that the capacity building of the private sector is also important, as Johkasou needs a periodic maintenance, in order to function properly.

2. Overview

Acknowledging the importance of proper treatment of wastewater generated in the rural area or specific buildings and facilities in the urban area which may cause adverse impacts on the water environment, as well as considering the fact that the Johkasou Technology has had advantages in improving water quality in Japan, and Japan has abundant experiences in managing wastewater especially in the rural area by utilizing Johkasou Technology, Both Sides see Johkasou Technology as fitting to be the center theme of the Joint Work, and seek to adopt Johkasou Technology to Indian buildings in as many areas as possible.

For the effective implementation of Joint Work, Both Sides will consult with each other to understand each side's circumstances in order to explore possible solutions. For that purpose, Both Sides will start holding a seminar as the first step of this Joint Work by communicating Both Side's situation relevant to the signed MOC, such as national policies and strategies, legal system for decentralized domestic wastewater

management, current status on domestic wastewater generation as well as its treatment and management, major problems or obstacles, and other information pertaining to water pollution. The seminar topics may include water quality monitoring system and its obtained data, etc., when appropriate.

3. Forms of Cooperation

(1) Seminars

- The first seminar will be held in virtual mode to share basic and wide-ranging information on decentralized domestic wastewater management and Johkasou, with presentations by experts to understand each activity in their own countries for further cooperation.
- After the successful completion of the first seminar, Both Sides proceed to the next step to hold seminars, the scope of which includes more specific theme raised by Both Sides.
- All the cost of the seminars will be borne by Japanese side, except for what is accrued internally in
 Indian side. It may include the cost for preparation of virtual format and coordination of the Indian
 speakers recommended from Both Sides.
- A seminar is expected to be held for 2 − 3 (two to three) hours. Due to the time difference between
 Both Sides, the Seminars will start in the morning in Indian time and in the afternoon in Japan time.
- (2) Capacity building (Training, Workshop and the other mode of such cooperation)
 - If one Side wishes to organize some training, workshop or other mode of cooperation for the capacity building, it will be well coordinated by Both Sides and adopted on mutually agreed basis.

(3) Pilot Project

- The details of pilot project are highlighted in Annexure II
- (4) Other forms of cooperation
 - If one Side wishes to organize other mode of cooperation, it will be well coordinated by Both Sides and adopted on mutually agreed basis.

4. Cooperating Partner

Each Side may designate a Cooperating Partner for supporting the implementation of each activity in various ways as mentioned in para 3 above.

The organization designated from the Indian side serves as the secretariat in implementing the activities carried out under this Joint Working Program, by putting a cell exclusively (hereinafter referred to as "Indian Secretariat"). The organization designated from the Japanese side also serves as the secretariat in implementing the activities carried out under this Joint Working Program, by commissioning from the Japanese side (hereinafter referred to as "Japanese Secretariat").

5. Beneficiaries

The implementation of the objectives of MOC, which is specified in this Joint Working Program, will help India achieve Sustainable Development Goals 6, target 6.3, while Japan will be benefited by way of helping India achieve the above-mentioned goal and target in this clause.

6. Role of Both Sides

Both Sides will bear an equally shared responsibility to manage and execute the Joint Work, which leads to Both Sides' necessity in obtaining the other side's consent if one Side wishes to initiate the Joint Work.

However, each Side has the right to propose and lead the Joint Work if it wishes so, after the concurrence of the other side. The latter will cooperate accordingly.

Both Sides will manage each side's participants represented by each government, and the venues if necessary, for the smooth implementation of the Joint Work.

7. Role of the Secretariat

The Secretariat will share draft Detailed Documents received from drafting Side to the other Side, after necessary clarification or adjustments of the text of the draft Detailed Documents in coordination with the drafting Side, subsequently further coordinate with the drafting Side by taking into consideration the comments received from the other Side, and then finalize the draft Detailed Documents for approval by Management Council. The Secretariat will undertake other necessary coordination in implementing the Joint Work.

7. Miscellaneous

Other terms and conditions are conformed to the signed MOC.

Annexure I

This Annexure I, describing the contents of the Joint Work in the form of a seminar, is treated as Detailed Document with the adoption by the Management Council, which was held on XX, XX, 2023. Subsequently, the Secretariat considers and finalizes the presenters and details such as title/contents/duration of each designated presentation.

< Contents for the Seminar>

- a) Introduction of current status of domestic wastewater treatment and its management for centralized and decentralized treatment system, presented by Both Sides.
- b) Video presentation on Johkasou (general overview and maintenance), presented by Japanese Side.
- Introduction of structure, function and performance evaluation testing system for the Johkasou, presented by Japanese Side.
- d) Introduction of legal system for decentralized domestic wastewater management in Japan including the Johkasou Act, presented by Japanese Side.
- e) Introduction of operation and maintenance, cleaning, inspection, license and sludge management for Johkasou, presented by Japanese Side.
- f) Introduction of technology and overseas business by Johkasou Manufactures, presented by Japanese Side.

Annexure II

This Annexure II, describing the contents of Joint Work in the form of a Johkasou pilot project. The scope of work of pilot project is not be administered by Management Council. However, as per point 4 of Paragraph IV of the signed MOC, Management Council may provide advice and support for Johkasou pilot project to be implemented by the Ministry of Jal Shakti.

In this regard, details of pilot project have been highlighted below:

- a) Name of the Promoter of pilot project: Ministry of Jal Shakti Government of India
- b) Technology of the pilot project: Johkasou
- c) Management Council consists of Both Sides, provides advice, and provides support only without incurring any cost for implementation.

6.2. 第1回会議体会合プログラム





1st Management Council Meeting Agenda

Date November 29, 2023

Time 12:30-14:30 IST in Indian time

 $(16:00 \sim 18:00 \text{ in Japan time})$

Venue Online via Zoom

https://zoom.us/j/91966917597

Participants Both sides of Management Council members and Associate members

Language Simultaneous interpretation (English / Japanese)

Agenda Items 1. Introduction on Both sides of Management Council members cum Approval of Associate members

2. Keynote Speeches (from both sides)

3. Approve the Joint Working Program and the 1st Seminar program

4. Presentation from the Associate members of both the sides

(Detailed Agenda is outlined on the subsequent page)

Detailed Agenda

Agenda Item	Personnel	Time (IST)	Time(JST)
Agenda Item 1 - Introduction on Both			
of Associate members			T. T. T. T.
Welcome address and brief introduction of	Shri Dheerai Joshi	12.30 p.m.	16.00
the members from the Indian side	Deputy Secretary, NMCG	12.00 p.m.	10.00
Welcome address and brief introduction of	Mr. Ryoma Sato	12.32 p.m.	16.02
the members from the Japanese side	Section Chief, Office for	Zie Z Piiii	10.02
and monitoris from the supunose site	Promotion of Johkasou		
Introducing the Agenda for 1st MOC	Both sides	12.35 p.m.	16.05
Meeting		12.55 p.m.	10.02
Agenda Item 2 - Keynote Speeches fro	m hath sidas	ı	
Keynote Address – Indian side	Shri Pradeep Kumar Agarwal	12.40 p.m.	16.10
Reynote Address – Indian side	Joint Secretary (NRCD)	12.40 p.m.	10.10
Keynote Address – Japanese side	Mr. Masaki Numata	12.50 p.m.	16.20
Reynote Address – Japanese side	Director, Office for Promotion of	12.50 p.m.	10.20
	Johkasou		
Agenda Item 3 - Approve on the Joint	The state of the s	aminar proa	ram
Introduce the Joint Working Program and	Ms. Thi Mai Hoang	01.00 p.m.	16.30
the 1st Seminar program	Senior Environment Expert of	01.00 р.ш.	10.30
lile 1st Semiliai program	Office for Promotion of Johkasou		
Discussions between MOC members from		01.02 p.m.	16.32
			10.32
Agenda Item 4 - Presentation from the Presentation from Arvind Envisol Ltd.	Mr. Amit Shah		16.45
		01.15 p.m.	10.43
(Temporary Member)	Head Global, Arvind Envisol Ltd.	01.20	16.50
Presentation from Sintex BAPL Ltd.	Mr. Naveena Nand Upadhyay	01.20 p.m.	16.50
(Temporary Member)	Deputy General Manager-R&D,		
Presentation from Daiki Axis India Pvt.	Design, Sintex BAPL Ltd. Mr. Kamal Tiwari	01 25	16.55
and the first of the contract		01.25 p.m.	16.55
Ltd. (Temporary Member) Presentation from Kubota Johkasou	CEO, Daiki Axis India Pvt. Ltd.	01.20	17.00
	Mr. Yoshito Kitai, Deputy	01.30 p.m.	17.00
System Co., Ltd. (Temporary Member)	Manager,		
Presentation from FujiClean Co.,Ltd	Kubota Johkasou System Co., Ltd. Mr. Yosuke Tabata, Ph. D.,	01.35 p.m.	17.05
(Temporary Member)	Executive Officer, Overseas	01.33 p.m.	17.03
(Temporary Member)	Business Group, FujiClean Co.,Ltd		
Presentation from Daiki Axis Co., Ltd.	Mr. Kazuo Saeki, Ph. D.,	01.40 p.m.	17.10
(Temporary Member)	Manager, Daiki Axis Co., Ltd.	01.40 p.m.	17.10
Presentation from Housetec Inc.	Video broad cast	01.45 p.m.	17.15
(Temporary Member)	Video broad east	01.45 p.m.	17.15
Presentation from Hiyoshi Corporation	JECES will introduce the website	01.50 p.m.	17.20
(Temporary Member)	of the company briefly	01.50 p.m.	17.20
Announcement from the secretariat	or and company offerry	1	
Confirmation items and future steps	Secretariat of Japan side	01.55 p.m.	17.25
• Schedule for the Seminar	Secretariat of Japan side	01.55 p.m.	17.23
• Schedule for the 2 nd MCM			
Vote of Thanks	1	1	L
Vote of Thanks, Indian Side	Deputy Secretary, NMCG	02.00 p.m.	17.30
Vote of Thanks, Indian Side Vote of Thanks, Japanese Side	Mr. Ryoma Sato	02.00 p.m. 02.03 p.m.	17.33
vote of Thanks, Japanese Side	Section Chief, Office for	02.03 p.m.	17.33
	Promotion of Johkasou		
	p romonon or jonkason	L	1

Objectives of the Management Council

The Management Council (MC) is established as per provision of the Memorandum of Cooperation signed between The Ministry of the Environment of Japan and The Ministry of Jal Shakti of the Republic of India (MOC) to implement this MoC by formulating detailed activities of collaboration and the monitoring of its progress.

Indian side of Management Council Members

No	Designation	Organization / Institution	Name
1	Joint Secretary	National River Conservation Directorate	Shri Pradeep Kumar
			Agarwal
2	Executive Director	National Mission for Clean Ganga	Shri Anup Kumar
	(Technical)	1000-10	Srivastava
3	Deputy Secretary	National Mission for Clean Ganga	Shri Dheeraj Joshi
4	Director (Technical)	National Mission for Clean Ganga	Dr. Pravin Kumar
5	Director, Swachh Bharat	Swachh Bharat Mission	Dr. Anupama
	Mission (G)		
6	Professor	Indian Institute of Technology Roorkee	Prof. A. A. Kazmi
7	Head of Chancery &	Embassy of India, Tokyo	Ms. Madhuri
	Political Officer	sas <u>5</u>	Gaddam

Japanese side of Management Council Members

No	Designation	Organization / Institution	Name
1	Director of Office for	Office for Promotion of Johkasou,	Mr. Masaki Numata
	Promotion of Johkasou	Waste Management Division,	
	(Leader –Japanese side)	Environmental Regeneration and	
	57 907	Material Cycles Bureau, Ministry of	
		the Environment Government of Japan	
2	Section Chief of Office for	Office for Promotion of Johkasou,	Mr. Ryoma Sato
	Promotion of Johkasou	Waste Management Division,	150
	(Sub Leader – Japanese	Environmental Regeneration and	
	side)	Material Cycles Bureau, Ministry of	
		the Environment Government of Japan	
3	Professor	Former Professor, Saitama University	Mr. Kiyoshi
	Knowledge Partner		Kawamura, Ph. D
4	Professor	Assoc. Prof, Research Center for	Mr. Ikuro Kasuga,
	Knowledge Partner	Advanced Science and Technology,	Ph. D
	7	The University of Tokyo	
5	Researcher	Manager, Planning Division	Mr. Yoshitaka Ebie,
	Knowledge Partner	(International Coordination Office), Ph. D	
		National Institute for Environmental	
		Studies (NIES)	
6	Senior Environment Expert	Office for Promotion of Johkasou,	Ms. Thi Mai
	of Office for Promotion of	Waste Management Division,	Hoang
	Johkasou	Environmental Regeneration and	
		Material Cycles Bureau, Ministry of	
		the Environment Government of Japan	
7	First Secretary	Embassy of Japan in India	Ms. Mihoko Nagai

Indian side of Associate Members (Temporary members)


No	Designation	Organization / Institution	Name
1	Head Global	Arvind Envisol Ltd.	Mr. Amit Shah
2	Deputy General Manager- R&D, Design	Sintex BAPL Ltd.	Mr. Naveena Nand Upadhyay
3	CEO	Daiki Axis India Pvt. Ltd.	Kamal Tiwari
4	Associate Professor/Director	Hokkaido University/ Global Land Programme	Dr. Ram Avtar

Japanese side of Associate Members (Temporary members)

No	Designation	Organization / Institution	Name
1.	Manager	Daiki Axis Co., Ltd.	Mr. Kazuo Saeki, Ph.
	10000	**	D
2	Executive Officer, Overseas	FujiClean Co.,Ltd	Mr. Yosuke Tabata,
	Business Group	7700 EV	Ph. D
3	Manager	Housetec Inc.	Mr. Koji Tsukamoto
4	Deputy Manager	Kubota Johkasou System Co., Ltd.	Mr. Yoshito Kitai
5	Chief, Research and	Hiyoshi Corporation	Mr. Kazuhiko Matsui
	Development Planning		
	Office		

6.3. 第1回会議体会合における発表資料

6.3.1. ジャル・シャクティ省の紹介





First Management Council Meeting

Ministry of Jal Shakti, Government of India and Ministry of The Environment, Government of Japan


Cooperation for Decentralized Domestic Wastewater Management

Under Namami Gange Programme three project with a total capacity of 1.92 MLD on Jhokhasou Technology has been sanctioned in Udham Singh Nagar, Rudraprayag and Rishikesh district of Uttarakhand

S. No.	State	Town	No. of STPs	Capacity (MLD)	AA&ES Cost Rs. In (Cr)
1		Udham Singh Nagar	3	1.3	199.36
2	Uttarakhand	Gaurikund & Tilwada	5	0.32	23.37
3		Muni Ki Reti, Rishikesh	1	0.3	94.06
	Total		09	1.92	316.79

Namami Gange Projects

Total capacity of 6,174 MLD (195 projects) is sanctioned under Namami Ganga up to October 2023



Namami Gange at a Glance

An integrated river rejuvenation mission for the Ganga River Basin

VISION: The Vision for Ganga Rejuvenation constitutes restoring the wholesomeness of the river defined in terms of ensuring "Aviral Dhara" (Continuous Flow"), "Nirmal Dhara" ("Unpolluted Flow"), Geologic and ecological integrity

Five pillars of Namami Gange



Components of the programme

Component	No of projects	Sanctioned Cost (Rs Cr)
Sewerage Infrastructure	195	31,344
Ghats and River front development	104	1,734
Solid waste management	12	295
Institutional Development	29	1,764
Research and public outreach	37	260
Biodiversity and Afforestation	51	764
Bioremediation	15	239
Rural sanitation	1	1,421
Others	6	200
Total	450	38,021

Historical moment for water management in India Formation of Ministry of Jal Shakti in 2019,

bringing all Major departments of the government dealing with water under the aegis of one Ministry







2014 -Implementation period ongoing Estimated budget (USD in Million) 4,000

2015 - 2020 2019 - 2024 2020 - 2026 2021-2026 2021 - 2026 3,000 50,000 790 17,000 8,000

Union Budget FY 2023-24, approx. USD 12 Billion allocated to Ministry of Jal Shakti

CATCH THE RAIN campaign in 2021 saw 4.8 million RWHS created/maintained at USD 9 Bn

Key schemes in sewage treatment – Namami Gange, SBM(G), AMRUT



Key Funding

Sources

Central government

Ministry of Jal Shakti

- Ministry of Housing and Urban
- Ministry of Environment, Forest and Climate Change; others

State governments State Urban development

- Rural water and sanitation departments
- PHED/ Municipal Corporations/ ULBs

International Financial Institutions

- · JICA
- The World Bank Group
- Asian Development Bank DFID; others





1st Management Council Meeting

Date	November 29, 2023	
Time	12:30-14:30 IST in Indian time (16:00 ~ 18:00 in Japan time)	
	Introduction on Both sides of Management Council members cum Approval of Associate members	
Agenda	Keynote Speeches (from both sides)	
Items	Approve the Joint Working Program and the 1st Seminar program	
	Presentation from the Associate members of both the sides	

6.3.2. インド側協賛メンバー Arvind Envisol Ltd.による発表







Arvind Limited, a part of The \$1.8 billion Lalbhai Group was incorporated in 1931 and is in the businesses of Textiles - fabric & garment manufacturing , Branded apparel & Retail , Environment Solutions, Agriculture, Engineering and Real Estate.

Established in 2011, Arvind Envisol is a world class water management company providing end to end solutions for water treatment, industrial waste water treatment, sewage treatment, zero liquid discharge solutions at minimal costs.





- Arvind STP & Septic Tanks are housed in specially designed highly durable FRP(Fiber Reinforced Plastic)
 Tanks, which are best suited for Sewage Applications.
- · Arvind FRP Tanks are made by using suitable polyester resin (Isopthalic Unsaturated Resin) and glass fiber.
- The tanks are specially designed for Under Ground applications have hollow ribbing of polymeric material
 encased on the outside of the tank with suitable polyester resin and fiberglass, to give lateral strength and
 extra protection. The tanks have shell thickness of 9.0±0.5 mm to make them capable to sustain an
 overburden of 2.30 meter of soil on top.
- Each Tank is Leak Proof & Corrosion Proof which makes it highly durable & best suited for making Septic Tank/STP/Collection Tank esp. for Underground Applications, with no chance for ground water contamination.
- Each Tank is Air-Tight making it suitable for maintaining Anaerobic conditions in Septic Tank & Package STP even if the above temperature is in sub-zero.
- Each tank is factory made and necessary tests are conducted before dispatch, so quality is ensured.





Process Principle of PSTP

Primary treatment:

Envisol

WERED BY ACVIDE

Pre-treatment removes materials that can be easily collected from the raw sewage before they damage or clog the pumps and sewage lines of primary treatment clarifiers (trash, tree limbs, leaves, branches etc.).

The influent sewage water passes through a bar screen to remove all large objects like cans, rags, sticks, plastic packets etc. carried in the sewage stream.

First stage transforms the solids in raw sewage to settled solids while allowing scum to float on the surface. It is a zone in which settled sludge is stabilized by anaerobic digestion wherein the F/M Ratio is maintained by returning activated sludge from the final sedimentation zone to the anaerobic zone. Due to anaerobic digestion the BOD reduction is around 30-40%

Water then enters anoxic zone and denitrification of the wastewater stream is accomplished. In the denitrification process, anoxic microbes break down existing nitrates, which results in the release of inert nitrogen gas into the atmosphere. Due to anoxic treatment free ammonia is achieved as per CPCB norms.


Secondary Treatment:

The sewage from the solid separation zone flows to the aeration zone. Air is diffused with help of air blowers which will encourage the growth of bacteria cultures in and around the Floating plastic media inside the aeration zone. The MBBR media provides extended surface area for growth of microorganisms. Due to aerobic digestion the BOD reduction is around 60-65%

The next step of treatment involves the sedimentation where organic wastes are settled in the zone. The settled waste in the bottom of the tank-is pumped back to the anaerobic zone as a return sludge, to ensure that quality of effluent would pass the stipulated sewage parameters.

Tertiary treatment:

The secondary treated sewage is then passed through Pressure Sand Filter where in suspended solid is removed around 90-95% & Activated Carbon Filter helps in further removal of color & Odor. The treated water is then disinfected using Sodium Hypochlorite dosing system which is an oxidation process, which in turns upports in further reduction of BOD levels before reuse.



COMPARISON OF ARVIND PACKAGE STP VS. CONVENTIONAL STP ENVISOR

Sr. No.	Properties	Prefabricated Arvind FRP-STP	Conventional STP in MSFRP/RCC
1	Technology	3rd Generation MBBR/Johkasou Technology	1 st Generation MBBR Technology
2	мос	Fiber Reinforced Plastic Tanks (FRP) Each Tank is Air Tight which makes it more stronger & durable especially for underground applications and suitable for maintaining anaerobic conditions	RCC/MSFRP.
3	Shell Thickness of Tank (Body)	9.5-10.5 mm (Tank can sustain more Overburden Capacity of Soil & indirectly can work at comparatively more Invert Level)	No standardization followed, Varies from contactor to contractor. Manipulation possible.
4	Application	Can be installed both above-ground & underground. No leakages as factory made and the MOC characteristics.	Can be installed on ground or below ground, however, leakages are very common in these tanks due to various reasons.
5	Partitions	Strong dish end curved partitions with stiffener	No standardization followed, Varies from contactor to contractor. Manipulation possible.
6	Minimum Load/Sewage flow	Works from no load to peak load. It is designed to take shock load for 4 hours in the morning & evening respectively	30 -40% minimum load required. Can take shock load of maximum 2 hours only

COMPARISON OF ARVIND PACKAGE STP VS. CONVENTIONAL	Envised
COMPARISON OF ARVIND PACKAGE STP VS CONVENTIONAL	CLDCI AITO
COMPARISON OF ARVIND FACINGESTE VS. CONVENTIONAL	POWERED BY ACVIOD

Sr. No.	Properties	Prefabricated Arvind FRP-STP	Conventional STP in MSFRP/RCC
1 11	Yearly Treatment Efficiency	Consistent efficiency throughout the year.	Seasonal variation is observed
12	Monitoring	No monitoring of MLSS & F/M ratio	Constant monitoring of MLSS is required.
13	Sludge Handling	Sludge handling required once in year.	Sludge handling once in 15 – 30 days
14	Supervision	Skilled supervision not required.	Continuous skilled monitoring required.
15	Electrical Consumption	50%-70% electrical saving compared to conventional STP	It consumes higher electricity than Arvind STP
16	MOC Depreciation	Leak proof, no root integration and no fungal growth	The Material of Construction causes fungal growth and leaks after 1 year
17	Project timeline	Installation lead time within a week to 15 days.	Construction work takes around four -six months
18	Upgradation	It can be upgraded and relocated.	No such scope available
19	Life	FRP tank life is more than 40 years.	Life of the system around 10 years

Sr. No.	Properties	Prefabricated Arvind FRP-STP	Conventional STP in MSFRP/RCC
7	Anoxic Zone	Additional Anoxic Zone facilitates Nitrogen & Phosphorous removal achieved in treated sewage parameters is as per PCB/NGT Norms	Denitrification process is very slow and not as effective required as per the requirement Govt. guidelines
8	Sludge Recycling	Activated sludge is pumped back in anaerobic zone every 2 hours for 2 minutes from final sedimentation zone. This helps in increasing the effectiveness of the system by reducing sludge & 0&M	9
9	Hydraulic Retention Time	Tank capacity is more. HRT is 18-22 Hr, (BOD, COD & TSS removal efficiency increases)	Tank capacity is less. HRT is 8-16 Hours (BOD, COD & TSS Removal efficiency comparatively low)
10	Air Blower Type	Ring Blower (02 stage) (Low maintenance cost consumes less electricity, no oiling & greasing required for these blowers, decibel is 40-50 dB)	Twin Lobe Blower (High Maintenance Cost along with regular oiling & greasing, consumes more electricity. So comparatively higher O&M costs)
















emamî



Radisson

MILACRON®
We Build Productivity

AND MANY MORE...



6.3.3. インド側協賛メンバー Sintex BAPL Ltd.による発表









0.3%

31% Ice & Permanent Groundwater Snow

Lakes & Rivers





Water Crisis

India is the second most populous country in the world, with more than 1 billion citizens. The scale of safe water need in India is immense, Many locations in India face water scarcity, thus it becomes necessity to store the water.

About 26% of India's population practices open defecation, a critical factor contributing to water-borne illness, stunting, and death.

These factors have created unprecedented urgency to implement effective solutions, to increase access to safe water.



WE HAVE PLAYED A SIGNIFICANT ROLE IN INDIA'S PROGRESS TOWARD IMPROVED WATER AND SANITATION, EMPOWERING MILLIONS OF PEOPLE WITH ACCESS TO SAFE WATER.






WHY STP NEEDED ??

The main goal of a sewage treatment plant is to treat the Wastewater and make it safe for human and environmental contact. Physical processes can either treat the Wastewater like solid-liquid separation or biological functions like aerobic digestion.

A sewage treatment plant needs to meet several requirements, including withstanding environmental factors like weather and earthquake zones. It also needs to have the capacity to treat Wastewater, be energy efficient, and produce a minimal amount of

It is a system that is used to clean and purify Wastewater that is discharged into the environment. The main goal of a sewage treatment plant is to protect the environment from water pollution by removing contaminants such as bacteria, nutrients, chemicals and particulates. Whether it is from a commercial building or industrial site, wastewater needs to be cleaned before it is discharged. A sewage treatment plant can help with this process.





Merits of Decentralized STP





A decentralised Sewage Treatment approach ensures treatment of wastewater close to the point of generation thus saving Power & Cost as there is no need to Pump the Sewage to a distant centralised location.

A Centralised STP needs skilled manpower for operations unlike a Sintex STP which functions without the need of any operator.





VARIOUS PACKAGED STP SOLUTIONS AVAILABLE WITH SINTEX

With Material	With Technology
ROTOMOULDING POLYETHYLENE TANKS -CPAPCITY RANGES (1.2 KLD to 6 KLD)	Moving Bed Bio Reactor (MBBR)
FIBRE - REINFORCED PLASTIC- FRP (CHOP HOOP WINDING PROCESS) CPAPCITY RANGES (10 KLD to >150 KLD)	




WELSPUN GROUP Leading Tomorrow Together

FEATURES OF SINTEX PACKAGED STP:

- Process: Dual filtration using aerobic and anaerobic water treatment process helps in achieving required level output in terms of BOD, COD, STT etc.
- Decentralized: It is a better investment in terms of energy consumption and efficiency when compared to a centralized wastewater treatment.
- Durability / Lifespan: FRP based material that is durable (Rustproof, leak-proof, RIB design etc) and lightweight, combined with technology requiring little intervention in terms of maintenance provides the system with a long life span of 50 years.
- Leadlime: The system is composed of pre-fabricated components optimizing packaging, transportation and installation. The complete system can be installed within few days in compared to other alternate which might take months.
- > Relocation: The option of relocation is available with Sintex PSTPs unlike other alternates.
- Easy Operation at less cost: The system works on gravity requiring less pumping, auto mode working of pumps and the sludge removal intervals are as high as 2 years making it less prone to maintenance. Also no special skills are required to operate the system.
- > Odorless: Sub ground structure makes it less prone to odor, occupant friendly.
- Zero foot print: Our STPs are sub-round structures occupying almost no space on the ground other than small pump round structures are mostly eyesore to the occupants.

Sintex PWTS is based on MBBR TECHNOLOGY similar to ZOHKASU TECHNOLOGY

This technology is essentially the same as activated sludge except that the media suspended in the reactor offers additional surfaces for the microbes to grow and this in turn maximizes the growth of microbes in a given volume of aeration tank compared to the conventional aeration without the media and to that extent, it does appear preferable. Diffused aeration is of course needed.



MBBR-MEDIA, SPECIAL MADE IN SINTEX HOUSE

With Bio Film





Sintex

WELSPUN GROUP Leading Tomorrow Together

NBF Series-Packaged Sewage Treatment Plant

Compacts System designed in a Single FRP/LLDPE **shell divided in compartment** which converts Sewage to re-usable water

Based on Advanced MBBR Technology

Reduces BOD (Biological Oxygen Demands) up to **95%**


No-Leakage in the tank hence no soil pollution

Completely **concealed system**, Noodor released directly to the environment

Easy to Install, operate and Easy to Relocate

Since it is installed underground hence maximum utilization of ground Surface







OPERATION PRINCIPLE

1 Solid Separation Zone (Anarobic Zone)

First stage fronsforms the influent solids to settled solids while allowing soum to float on the surface. It is a primary sedimentation zone in which settled studge is stabilized by anaerable digestion. The treatment efficiency of the chamber is in the range of 30% 80D removal.

2 Aeration Zone (Aerobia Zone)

Second stage is the aerobic zone along with plastic media raided the tank which in turn increases the surface area and retains micro-organism long enough to digest the organic substance. Cliear water overflows to the next featurent chamber. At is provided through blowers and higher contact time with the 8io-film on the plastic media facilitates efficient digestion. 8CD removal is around 40%.

3 Final Sedimentation Zone


Final stage involves sadimentation where organic waste are settles in the sedimentation zone. The settled waste in the bottom is pumped back to the solid separation zone as a return studge having active biomass (MLSS) to increase the efficiency of the system. The output from this zone is effluent from meets the stipulated PCSs Sandards.

4 Optional

For more Stringent effluent parameter, we also offer Tertiary Treatment Plant (TTP) addition to the system which does the job of filtration that further improves effluent.



Working Flow Diagram of PSTP's (NBF SERIES)



1. INFLUENT

2. BAR SCREEN CHAMBER

3. ANAEROBIC & ANOXIC ZONE

4. AEROBIC MBBR ZONE

5. FINAL SEDIMENTATION

6. FILTER FEED TANK

7. MBBR MEDIA

8. AIR BLOWERS 9. RECIRCULATION PUMP

10. FILTER FEED PUMP

11. PRESSURE SAND FILTER
12. ACTIVATED CARBON FILTER


13. DISINFECTION

14. AIR VENT

15. TREATED WATER TANK



WELSPUN GROUP





Advantages

Sintex PSTP vs other STP

Sr. No.	Prefabricated Sintex FRP-PSTP	R.C.C./ MSFRP - Conventional STP
1	Aesthetic appearance.	Cleanliness is compromised due to foul smell and flies.
2	leak proof, no root integration and no fungal growth.	Possible in Conventional STP.
3	Installation lead time within a week.	Construction work takes around six months.
4	It can be upgraded and relocated.	No such scope available.
5	FRP tank life more than 30 years.	Life span is lesser than 20 year.
6	It can be an excellent solution, since it is a standalone process.	We may get some dead mass in clear supernatant which increases the filter load.
7	Uses High Porosity moving media for bacteria to grow.	Appropriate aeration and decanting is essential for the correct operations of these plants.
8	Useful for modification / capacity extension of existing STP.	Not applicablefor any modification.
9	Increased SRT and hence well nitrified effluent and low sludge volumes.	No such scope available.



Best Fit For

- Industrial
- PSU's
- Residential and Commercial Complexes
- > Public buildings and Government offices
- > Hospitals and Hotels and Motels
- > Colleges and educational institutes
- Farm Houses Bungalows
- Holiday resorts & clubs
- Ware houses
- Automobile sector





Results Delivered By Our System

1. W/O Tertiary Treatment Plant:


Sr. No.	Parameters	If Inlet	Then Outlet
1	рН	6.5 - 8.5	6.5 - 8.5
2	BOD	250-300 mg/l	< 30 mg/l
3	COD	400-600 mg/l	< 150 mg/l
4	TSS	200 mg/l	< 50 mg/l
5	FOG	40-50 ppm	< 5 mg/l

Treated Water Use - Irrigation & Gardening Landscaping Purpose

2. W/O Tertiary Treatment Plant:

WELSPUN GROUP

Sr. No.	Parameters	If Inlet	Then Outlet
1	рН	6.5 - 8.5	6.5 - 8.5
2	BOD	250-300 mg/l	<10 mg/l
3	COD	400-600 mg/l	< 50 mg/l
4	TSS	200 mg/l	< 10 mg/l
5	FOG	40-50 ppm	< 5 mg/l
5	FOG	40-50 ppm	< 5 mg/l



Sintex





Raw

Sewage





	Specification							Mod	del								
		NBF-10	NBF-15	NBF-20	NBF-25	NBF-30	NBF-35	NBF-40	NBF-45	NBF-50	NBF-60	NBF-70	NBF-80	NBF-90	NBF-100	NBF-120	NBF-15
	Residential (150 lpcd)	67	100	133	167	200	223	267	300	333	400	467	533	600	667	800	1000
No. of Users	Office (80 lpcd)	125	187	250	312	375	437	500	562	625	750	875	1000	1125	1250	1500	1875
	Toilet (50 lpcd)	200	300	400	500	600	700	800	900	1000	1200	1400	1600	1800	2000	2400	3000
	Educational Institutions (80 lpcd)	125	187	250	312	375	437	500	562	625	750	875	1000	1125	1250	1500	1875

LPCD: Litres per capita per day.

Salient Features of PSTP-NBF System

Sintex

Salient Features of PWTS STBF System

			NUMBER OF USERS						NSIONS		
SR. NO	MODEL	RESIDENTIAL (150 IPCD)	OFFICE (80 IPCD)	EDUCATIONAL INSTITUTIONS (80 IPCD)	TOILET (50 IPCD)	CANTEEN (20 IPCD)	DIAMETER (MM)	HEIGHT (MM)	INLET/OUTLET PIPE (MM)	VENT (MM)	
1	PWTS-STBF-0120- 01	6	8	8	16	30	1300	1400	100	50	
2	PWTS-STBF-0160- 01	10	13	13	22	50	1440	1560	100	50	
3	PWTS-STBF-0180- 01	12	15	15	24	60	1490	1615	100	50	
4	PWTS-STBF-0200- 01	14	18	18	28	70	1540	1640	100	50	
5	PWTS-STBF-0300- 01	16	23	23	46	80	1830	1880	100	50	
6	PWTS-STBF-0400- 01	20	26	26	52	100	1900	2020	100	50	
7	PWTS-STBF-0500- 01	24	33	33	66	120	1970	2280	100	50	
8	PWTS-STBF-0600- 01	32	40	40	80	160	2070	2330	100	50	









MATERIAL OF PACKAGED SEWAGE TREATMENT PLANT

Material of Sintex PSTP's							
Sr.	Description	Material					
1	Sintex FRP base Tank/STBF	Fibre Reinforced Plastic/LLDPE	Т				
2	Inlet Outlet Socket	U-PVC					
3	Air vent , Aeration Socket ,Pump Socket	U-PVC	П				
4	Fastener of Manhole cover	s.s.					
5	Manhole Cover (Dia550 & 750 mm)	M.S. with Epoxy Coating					
6	Manhole with Hole	FRP	Т				
7	Deadman	RCC	Т				
8	Strap	FRP					
9	Turn Buckle	G.I.	Т				
10	Clamp	G.I.	П				
11	Ribing	U-PVC	Т				
12	Fastener for Strapping	G.I.					
13	Sludge Re-circulation Pump	-					
14	Blower for Aeration	Low power Consumption/Imported Quality					
15	Header for Blower	M.S. with Epoxy Coating					

WELSPUN GROUP





Production Facility & Process

- We have skilled team capable of producing both LLDPE and FRP tanks
- One of the Best Chop Hoop Winding Process for FRP Material which is Limited in India.
- One of the largest rotomoulding process house



WELSPUN GROUP

(A) THE FRP UG TANK PROCESS (CHOP HOOP WINDING PROCESS).

- The chop hoop process is a variation on the filament winding technology. Chop hoop is in fact & combination of a winding process and spray up.
- The Technique is used for the production of cylindrical storage tank.
- (B) Rotomoulding process for producing vertical and horizontal LLDPE tanks for PSTP and water storage solutions













DREAMS KITCHEN MODERN ENTERPRISES SYLOG ENTERPRISES PRIVETE LIMITED

Installation of PSTP - NBF System









Filling with gravel size 4.5 to 12.5 mm

Contd.









Unloading of the System

Refilling of trench

Piping Work

Blowers in room









Triple Benefits to clients






Land Saving: As the system goes underground above space can be used for gardening purpose or as parking lot.

Beautification: As the system is odor free a children park can be there on top of the system.

Responsibility: Individual responsibilities can be easily given to the owners of the scheme.

Central Pollution Enrollment Copy





Sintex PSTP MBBR Technology In **CPHEEO Sewage Manual** Prepared By Central Ministry Of Urban Development Since 2012



46





Approval from Military Engineering Services







List of Customers
















































Scheme designs for different type of users based on Johkasou technology




STRICTLY PRIVATE AND CONFIDENTIAL

STRICTLY PRIVATE AND CONFIDENTIAL

Few Case Studies from India



AXIS



NAGPUR - NMC Nevendra Fadnavis 🥝 @Dev_Fadnavis - Aug 15 edicated 3 of the total 12 Mini STPs (Sewage Treatment Plants) by agonme to Nagpurkars with our Hon Union Minister @nitin_gadkari ji & Mayor Dayashankar Tiwari & other public representatives were present on







Johkasou @ Delhi DDA Park

Sewage lifting from drainage line

- ✓ BOD: 200 >> 8
- ✓ COD: 350 >> 35 ✓ TSS: 280 >> 12
- DDA have 50 plants installed working since 2021
- Impact:

10

- Saving of 900 Million Litres of ground water every year.
- . 1000 Acres of Green Area covered in Delhi.
- Revival of many water bodies
- · Reducing load of 900 million waste water
- flowing into river Yamuna
- Execution Period Less than one year



STRICTLY PRIVATE AND CONFIDENTIAL













Nitin Gadkari 🔮 @nitin_gadkari - Aug 15

Devining a distance of the many and the second devined devined and the second devined devin

♡ 450

t] 98

STRICTLY PRIVATE AND CONFIDENTIAL

Decentralized wastewater management in a campus - NTPC, Mouda



Centralized STP

Total CAPEX : 12crore

- · STP (1 Location)
- Piping 2.5km OPEX :
- · 2 operators
- · Total 12.50kW

De-centralized STP

Total CAPEX: 3crore

- · STP (6 Location)
- Piping 0.2km OPEX :
- No operator
- Total 1.75kW (Less transfer)

STRICTLY PRIVATE AND CONFIDENTIAL





AXIS

STRICTLY PRIVATE AND CONFIDENTIAL

AXIS

AXIS

STRICTLY PRIVATE AND CONFIDENTIAL

Site references under the Green area





Certification and Awards

■ Daiki Axis India brought Johkasou concept in India and spread and educate it to India. Installed more than 700 Johkasou in India







AXIS

STRICTLY PRIVATE AND CONFIDENTIAL

AXIS

JOHKASOU-STP factory in Vapi, Gujarat

■ Johkasou-STP factory in Japan & India (Gujarat)



STRICTLY PRIVATE AND CONFIDENTIAL







AXIS

STRICTLY PRIVATE AND CONFIDENTIAL

Daiki Axis India started Johkasou Skill Development Program

■ Daiki Axis follow Indian Government program in this important and growing area under Swachh Bharat, Skill development Program for STP Operators based on Japanese Johkasou skill development templated is already started ...




Key Challenges & Opportunities

- ❖ Error Products. Johkasou need to compete in the market against poorly designed and made products available at very low prices... - We are working with BIS to finalize Standard in next few months.
- ❖ Misuse of Johkasou Name- Me too.. Several local companies selling copy or unauthorized Johkasou products... - Need to consider how to stop misuse of Johkasou name in India...
- ❖ Lack of systematic eco-system development, low user awareness, standard and too many alternatives . Johkasou type Act and integrated plan is needed in India to organize the area..
- ♦ Low market volume, and High Freight and Tax structure , 30-40% cost gets added by Freight and Taxes..
- ❖ Low enforcement of compliance MC can suggest some policy incentive or methods to improve compliance as it will help in faster development and cost reduction.
- ❖ Quality and Skill level of construction and O&M. MC can support to accelerate the training and skill development program already started by DAI & SVSU...




6.3.5. 日本側協賛メンバー クボタ浄化槽システム株式会社による発表


















Advantages of Kubota Johkasou

For Earth, For Life

- ${\bf 1.} \ {\bf Kubota\ has\ a\ history\ of\ more\ than\ 50\ years\ since\ it\ started\ manufacturing\ and\ selling\ Johkasou.}$
- 2. Quality of treated water by "Johkasou" is same as that of sewerage systems.

(BOD removal ratio \geq 90%, Effluent BOD \leq 20mg/L)











For Earth, For Life

Kubota

9



Advantages of Kubota Johkasou

For Earth, For Life

3. We Kubota exports the same models of Johkasou certified in Japan.

Structure and function Approval of Johkasou type in Japan

•Performance tests [™] and approvals of the type (Minister of Land, infrastructure and Transport and Johkasou Law) are required for Johkasou.

※ Tested by the authorized third party







KZII (1.0 ~ 2.0 m3/day)

13/day) HCZ (2.8 ~ 10.0 m3/day)

K-HC-T (10.0 ~ m3/day)




Large-scale wastewater treatment tank



- Type : KM-SG-NP
- •Flow rate: about Max 500m³/day
- •Treatment process :

 Membreane bioreactor(MBR)
 process
- Size

2,500Φ X H2,800 mm











- 1) Johkasou will continuously produce high quality of treated water during long time by performing regular maintenance.
- 2) Maintenance of Johkasou includes 2 main works (checking and desludging).
- •Checking: checking operation of Johkasou to acknowledge when it is necessary to do cleaning in early stage.
- •desludging: removing sludge and scum stored inside Johkasou to restore treatment ability.
- 3)Not performing maintenance regularly will lead to reduce treatment ability and fail to produce expected quality of treated

For Ei For Earth, For Life Kubola Solution with Johkasou in Asia Factory, Building, etc., sewage in Myanmar











USA





FujiClean USA, LLC

41-2 Greenwood Road Brunswick, Maine 04011 U.S.A Phone: +1 207 406 2927 Fax: +1 207 406 2929 www.fujicleanusa.com

- ♦ Founded in July 2013
- ◆ CE models; certified to NSF40 CEN models; certified to NSF40/245
- ◆ 1st Manufacturing location; Brunswick, Maine 2nd Manufacturing location; Augusta, Georgia





Europe





Ammermann Umwelttechnik GmbH

Am Dobben 4, 26639 Wiesmoor,Germany Phone: +49 4944 6060 http://ammermann-gmbh.de

- ◆ Started business as FujiClean EU in 2017 CEN models; Certified to the EN 12566-3
- ◆ Manufacturing location; Wiesmoor, Niedersachsen







11

Australia







FujiClean Australia Pty. Ltd.

2/176 Siganto Drive, Helensvale Queensland 4212 Phone: +61 7 5580 0927 www.fujiclean.com.au

- ♦ Founded in January 2008
- ◆ ACE1200, ACE3000; Advanced Secondary system
 ✓ Certified to the latest Australian Standard 1546.3
- FujiClean system is available in all states.
- ◆ 1st Manufacturing location; Near Gold Coast, QLD 2nd Manufacturing location; Near Melbourne, VIC







The Other Countries














10







6.3.7. 日本側協賛メンバー 株式会社ダイキアクシスによる発表

Introduction to Daiki Axis Johkasou

Japanese Domestic Wastewater Treatment System



- Company Profile
- · Daiki Axis Johkasou
- Summary

Company Profile

Daiki Axis Co., Ltd.

Date Founded: 12th July, 1958

1,052 (December 31, 2022) Employees: Main business: Environmental equipment

Household equipment Renewable energy

Environmental equipment
















3

Company Profile - Johkasou factories in Japan





Company Profile – Overseas factories 5 2015 INDONESIA FACTORY 2022 Sri Lanka FACTORY 2018 CHINA FACTORY 2022 INDIA NCR FACTORY 2019 INDIA Vapi FACTORY DAIKI AXIS INDIA PRIVATE LIMITED CRYSTAL CLEAR CONTRACTOR PTE.LTD. PT.DAIKI AXIS INDONESIA DAIKI AXIS SINGAPORE PTE.LTD.

· Company Profile

- · Daiki Axis Johkasou
- Summary

Daiki Axis Johkasou

Paiki O AXIS

■ Johkasou is a de-centralized STP for domestic wastewater treatment, Daiki-Axis Manufacture, Sale, Install & Maintain it in Japan & All over the world




Inlet Pa	rameter	A I Outflow	A I J Outflow	A I M Outflow	
6-8	рН	6-8	6-8	6-8	
300	BOD	20	10	5	
450	COD	100	50	10	
240	SS	50	20	5	
50	0 & G	10	10	5	
50	T-N	45	20	10	



Daiki Axis Johkasou - Inside image and flow

8





Daiki Axis Johkasou – Project references

0

Under ground installation







Above ground installation









Summary

11

What Daiki Axis can provide...

- Technological capability based on 65 years experience
- Lower cost product compare than the product manufactured in Japan
- Total domestic wastewater treatment services

What Daiki Axis required

- Reconsideration of effluent water standard for Johkasou
- Strengthen the monitoring system (application → approval → monitoring)

- · Company Profile
- · Daiki Axis Johkasou
- Summary







Joint Work in the form of a Seminar

Date Tuesday, 19 December, 2023

Time 11:30 AM ~ 1:30 PM in Indian time

(3:00 PM ~ 5:00 PM in Japan time)

Venue Online via Zoom Webinar

Language Simultaneous interpretation (English / Japanese)

Program

1. Opening remarks from both side

Items

2. Presentation

3. Closing

(Detailed Program is outlined on the subsequent page)


Detailed Program

Program Item	Personnel	Time -IST (min.)	Time - JST
Program Item 1 - Opening remarks from	both side		
Opening remarks – Japan side	Mr. Masaki Numata	11:30 a.m.	15:00
	Director of Office for	(5)	
	Promotion of Johkasou		
Opening remarks – Indian side	Shri. Pradeep Kumar	11:35 a.m.	15:05
	Agarwal	(5)	
	Joint Secretary (NRCD),		
	Jal Shakti		
Program Item 2 - Presentation			_
Introduction of current status of domestic	Shri Dheeraj Joshi	11:40 a.m.	15:10
wastewater treatment and its		(10)	15.10
management for centralized and	Deputy Secretary, NMCG	(10)	
decentralized treatment system in India	along with Shri Shubham		
	Tiwari, DTL-PMC, NMCG		
Introduction of current status of domestic	Mr. Ryoma Sato	11:50 a.m.	15:20
wastewater treatment and its	Section Chief of Office for	(7)	
management for centralized and	Promotion of Johkasou		
decentralized treatment system in Japan	M. D. G.	11.57	15.07
Introduction of legal system for decentralized domestic wastewater	Mr. Ryoma Sato	11:57 a.m.	15:27
management in Japan including the	Section Chief of Office for	(8)	
Johkasou Act	Promotion of Johkasou		
Introduction of operation and	Mr. Shinhi Kumokawa, Ph. D,	12:05 p.m.	15:35
maintenance, cleaning, inspection, license	Japan Education Center of		15.55
and sludge management for Johkasou		(8)	
	Environmental Sanitation		
0.0.1	(JECES)	10.10	4 7 40
Q&A		12:13 p.m.	15:43
		(14)	2000 0000
Break		12:27 p.m.	15:57
	_	(5)	
Introduction of structure, function and	Mr. Yosuke Tabata, Ph. D,	12:32 p.m.	16:02
performance evaluation testing system for	Executive Officer, Overseas	(8)	
the Johkasou ~e.g. case study from Japan,	Business Group, FujiClean		
US, and Australia~	Co.,Ltd		
Introduction of estimation method of	Mr. Yoshito Kitai,	12:40 p.m.	16:10
Population equivalent (PE) for	Deputy Manager , Kubota	(8)	
decentralized wastewater treatment	Johkasou System Co., Ltd.	(-)	
plants in Japan			
Practice of installation work of Johkasou	Mr. Kazuo Saeki, Ph. D,	12:48 p.m.	16:18
in Japan and overseas countries	Manager, Daiki Axis Co., Ltd.	(8)	
Q&A		12:56 p.m.	16:26
		(19)	
Program Item 3 - Closing		**************************************	
Closing remarks from Japan side	Mr. Ryoma Sato	1:15 p.m.	16:45
	Section Chief of Office for	(3)	
	Promotion of Johkasou		
Closing remarks from Indian side	Control and the Control of the Contr	1.10	16,40
oroning remarks from matan side	Shri Anup Kumar	1:18 p.m.	16:48
	Srivastava,	(3)	
	Executive Director (Technical),		
	NMCG		
	End of the Seminar	1:21 p.m.	16:51

Note - TBC- To be confirmed

6.5. セミナーにおける発表資料

6.5.1. インド側(NMCG)のセミナー発表資料(Current Status of Domestic Wastewater Treatment & Management (for centralized and decentralized treatment system) in India)




Namami Gange at a Glance

				Sanc	tioned				Completed	
S. No.	Type of Project	Name of State	No of Projects	Capacity (MLD)	Network (km)	Cost (in Rs. Cr)	Expenditure (Rs. Cr)	No of projects	MLD Created/ Rehabilitate d	Network (km
1		Uttarakhand	42	244	208	1,717	767	36	165	175
		Uttar Pradesh	69	2,388	1,896	14,097	5,345	37	945	1,799
		Bihar	37	745	1,792	6,160	3,850	13	274	1,305
		Jharkhand	5	262	151	1,310	186	2	16	88
		West Bengal	28	899	982	4,834	1,742	11	379	859
	Sewerage Projects	Haryana	2	145	41	218	218	2	145	52
		Delhi	9	1,268	37	1,951	1,812	7	704	36
		Himachal Pradesh	1	2	0	12	4	1	2	0
		Rajasthan	1	36	146	258	176	0	36	135
		Madhya Pradesh	2	219	20	604	0	0	0	0
		Modular STP Decentralized	-1	0	0	410	0	0	0	0
		Total	197	6,208	5,272	31,571	14,100	109	2,666	4,449
3	River	front, Ghats and Crematoria	105	-	.77	1,735	1,212	79	-	
4	S	olid Waste Management	12		-	295	192	9	-	H=1
5	Institutional	Development (Non-Infrastructure)	29		123	1,764	508	9		22
6	Project Implementation Support, Research and Study Projects, Public Relations and Outreach		37		144	260	42	8	()	-
7	Biodiversity, Afforestation and Bioremediation		66	-	855	1,003	477	40	-	
8		Other Projects	8		144	1,756	1,186	5	-	440
		Grand Total	454	6,187	5,254	38,384	16,834	259	2,666	4,449

Ganga River Basin- Project Details

Total capacity of 6,187 MLD (197 projects) is sanctioned under Namami Ganga up to October2023

Time Period	Sewage Capacity Created/to be Created (MLD)
Completed April 2014 – December 2021	993
Completed January 2022 – November 2023	1,672
Completion Planned December 2023 – March 2026	3,522
Total	6,187



Total targeted capacity by Dec' 2026: 7,001 MLD (Including New Projects to be Sanctioned)

Transformational Initiatives Under Namami Gange

Governance for long-term sustainability of Sewerage Assets

Hybrid Annuity Based PPP model

Used to undertake projects involving the construction of STPs and interception and diversion works, under the Namami Gange programme. A total of 33 projects in Ganga river basin towns/ cities have been sanctioned

One city one operator model

- Shift towards a one-step solution for entire city Integration of new and existing sewerage treatment
- infrastructure under HAM model Single ownership and accountability for end-to-end operations
- Ensure continued performance for existing and new sewerage infrastructure









Photos of Operational Nirmal Jal Kendras (NJKs)/STPs in Uttarakhand



Devprayag 1.40 MLD NJK (STP)



Rishikesh (Swargashram) 3 MLD NJK (STP)



Chorpani 7.5 MLD NJK (STP)









Srinagar 3.5 MLD NJK (STR)

Photos of Operational Nirmal Jal Kendras (NJKs)/STPs in UP



Masani, Mathura 30 MLD NJK (STP)

Ramanna , Varanasi 50 MLD NJK (STP)



Kodra, Prayagraj 25 MLD NJK (STP)



Rajapur , Prayagraj 90 MLD NJK (STP)



Ramnagar , Varanasi 10 MLD NJK (STP)



Moradabad 58 MLD NJK (STP)

Photos of Operational Nirmal Jal Kendras (NJKs)/STPs in Bihar





Beur, Patna 43MLD NJK (STP)



Karmalichak, Patna 37MLD NJK (STP)







Maner, Patna 6.5MLD NJK (STP)



Chhapra 32MLD NJK (STP)

Photos of Operational Nirmal Jal Kendras (NJKs)/STPs in W.Bengal



Barrackpore 24 MLD NJK (STP)



Halishahar 16 MLD NJK (STP)



Budge Budge 9.3 MLD NJK (STP)



Kalyani 21 MLD NJK (STP)



Bhatpara 41 MLD NJK (STP)

PRAYAG: Monitoring Centre at NMCG

- Inaugurated on 20th April 2023 by Hon'ble Minister of Jal Shakti, Government of India
- PRAYAG (Platform for Real time Analysis of YamunA, Ganga and their tributaries) is a Real Time
 Monitoring Centre with on-line dashboards for planning and monitoring of project progress through
 real time feeds, river water quality, Performance of STPs, PMT Tool Dashboard, Ganga Districts
 Performance Monitoring System.






Major Achievements of Namami Gange Program Launched in 2014

Notable Improvement in River Water Quality, increase in numbers of Gangetic Dolphins and other biodiversity indicators

97 Manual and 76 Real Time Water Quality Monitoring Stations (RTQMS) are operational for monitoring water quality



	Polluted Stretches	Priority Category		
State	Polluted Stretches	2014-15	2022 (Jan to Sept)	
Uttarakhan	Haridwar to Sultanpur	V	Not Polluted	
d		(4.2 - 5.8 mg/l BOD)	(< 3 mg/I BOD)	
Uttar	Kannauj to Varanasi	III	V	
Pradesh		(3.8 - 16.9 mg/I BOD)	(2.5– 4.7 mg/l BOD)	
Bihar	Buxar to Bhagalpur	II (7.8 - 27 mg/I BOD)	Not Polluted (< 3 mg/l BOD)	
West	Triveni to Diamond	V	V	
Bengal	Harbour	(3.1 - 5.8 mg/l BOD)	(2.6 – 3.9 mg/l BOD)	

1	BOD > 30 mg/l
II	BOD: 20-30 mg/l
III	BOD: 10-20 mg /l
IV	BOD : 6-10 mg/l
V	BOD: 3-6 mg/I

In 2022, No Stretches of River Ganga in Priority I to IV Categories of pollution

Achievements and Accolades

GANG

Namami Gange Mission: Recognized as one of the TOPTEN "World Restoration Flagship" by UN Decade



- DG, NMCG receiving the Award from Ms Natalia Alexeeva, UN Decade on Ecosystem Restoration
- 2021 2030 declared as the Decade on Ecosystem Restoration by UNGA, positioning restoration of ecosystems as a major nature-based solution for achieving SDGs & national priorities
- World Restoration Flagships of the UN Decade are the first, best, or most promising examples of largescale and long-term ecosystem restoration in any country or recion.
- Led by UNEP and FAO, it embodies 10 Restoration Principles of the UN Decade

Participation in UN Water Conference - 2023



- The Only Indian entity to Organize a side event in the UN HO during the UN Water conference. Nammal Gange —
 "Namami Gange - An integrated & holistic approach towards Conservation & Rejuvenation of River Ganga and it's Ecosystem" was well attended
- Bilateral meetings held with 13 countries Denmark, Egypt, European Union, France, Israel, Vietnam, Canada, Indonesia, United Kingdom, Singapore, UAE Japan and Bangladesh

14

Achievements and Accolades

GANG

NAT-GEO Award

A GOLDEN MOMENT TO FRAME. A GOLDEN MOMENT TO FRAME. GENGA - RIVER FROM THE SKIES BEST DOCUMENTARY BEST CORENTARY BEST CHERRY AFFAIRS BEST HATURAL HISTORY OR WILDLIFE FROGRAMME

Meeting of EDs of World Bank in Agra



Meeting held in Agra on 5th August 2023:

As part of the visit of 12 Executive Directors (EDs) of World Bank, representing 100 countries, to see the transformational progress of India and some World Bank funded projects in India, a meeting was organized on 5 August, 2023 in Agra in which Director General, NMCG, Mr. G. Asok Kumar gave a detailed presentation. Mr. Auguste Kouame, Country Director, World Bank, India was also present on the occasion.

Wastewater Generation & Wastewater Treatment Capacity in India

India's regulatory framework for wastewater treatment is evolving, with promising policies

Current Laws & Regulations covering WWT

Environment (Protection) Act, 1986: Water (Prevention & Control of Pollution) Act, 1974:

Environmental Impact Assessment Notification (2006):

Water Cess Act (1977):

Municipal Solid Waste (Management & Handling) Rules, 2000:

Existing Policies

National Water Policy (2012) mandates setting up of sewage treatment plants in all towns with a population exceeding 10,000

Fecal Sludge and Septage Management FSSM (2017): Recognizes synergies and potential for co-treatment options for sludge.

National Framework for Safe use Treated Wastewater

Offers guidelines for the formulation of State reuse policy and intends to build appropriate market and economic models

Power Tariff Policy of 2016 mandates utilization of treated water from STPs at thermal power plants.

Efforts to bridge Gaps and Challenges

Coordination:

 Coordination challenges at various tiers causes uneven implementation which can be addressed by bringing together central and state level agencies

Integration:

 Untapped potential for wastewater reuse as a source for water bodies, groundwater recharge, and alternative water sources to be looked into

Decentralised Wastewater Treatment in India: Towards a National Framework



Decentralized Wastewater Treatment (DWT) is gaining momentum across states

National Water Policy (2012) incentivizes

- Decentralised sewage treatment plants,
- Recycling and reuse of treated water
- through planned tariff systems, and subsidized treatment of industrial effluents.
- · Scope for Decentralised Solutions
- The policy advocates Promotion of sanitation solutions that minimize water usage and treat wastewater at the source.

Several states including Karnataka, Kerala have taken steps towards adopting decentralised wastewater treatment solutions

Towards a National Framework

- NMCG's experience with the Ganga River basin fosters a comprehensive perspective that considers social, environmental, and economic aspects with expertise in implementing wastewater treatment infrastructure.
- The National Mission for Clean Ganga has promoted decentralized solutions such as Jhokasou for the Ganga River.

NMCG possesses the institutional knowledge and experience to craft a comprehensive national framework for decentralized wastewater treatment across India.

Jokhasou Technology and its adoption in certain NMCG projects

Under Namami Gange Programme three project with a total capacity of 1.92 MLD on Jhokhasou Technology have been sanctioned in Udham Singh Nagar, Rudraprayag and Rishikesh district of Uttarakhand

S. No.	State	Town	No. of STPs	Capacity (MLD)	AA&ES Cost Rs. In (Cr)
1		Udham Singh Nagar	3	1.3	199.36
2	Uttarakhand	Gaurikund & Tilwada	5	0.32	23.37
3		Muni Ki Reti, Rishikesh	1	0.3	94.06
		Total	09	1.92	316.79


Few examples of Decentralised Treatment Technology Adopted Across India

Decentralized wastewater treatment systems (DEWATS) offer a promising alternative to traditional centralized systems in India, particularly for smaller communities and areas with limited infrastructure. Diversity of DEWATS systems in terms of industry sectors, cost structures, output quality is presented in the table below


City	Location/Sector	Technology	Key Features
Koraput, Odisha	Hospital	Constructed Wetlands (CWs)	Treats wastewater for reuse in irrigation, low maintenance.
Puducherry, Tamil Nadu	College campus	CWs	High-quality effluent for reuse, eco-friendly and sustainable.
Mumbai, Maharashtra	Slum areas	Septic Tanks with Biofilters	Reduces BOD and COD levels, improves sanitation.
Bangalore, Karnataka	Gated communities	Decentralized Wastewater Treatment Plants with Biofilters	Non-potable water reuse, affordable and efficient.
Gurgaon, Haryana	Residential complex	Membrane Bioreactors (MBRs)	Stringent discharge standards, high-quality effluent for landscaping.
Chennai, Tamil Nadu	Hospital	MBRs	Meets stringent discharge standards, advanced technology for complex wastewater.
Gandhinagar, Gujarat	Dairy farm	Anaerobic Digestion (AD)	Biogas generation for energy, nutrient-rich digestate for agriculture.
Pune, Maharashtra	Food processing industry	AD	Biogas for cooking fuel, reduces environmental pollution.
Darjeeling, West Bengal	Hill resort	Community-Managed CWs	Reduces pollution, improves water quality, community ownership.
Kodagu, Karnataka	Rural communities	Decentralized Treatment Plants (community-managed)	Improved sanitation and hygiene, empowers communities.



6.5.2. 日本側環境省のセミナー発表資料 (Current Status of Domestic Wastewater Treatment and its Management for Centralized and Decentralized Treatment System in Japan)




Comparison of Sewage, Johkasou and Septic tank Sewage (STP) Johkasou Septic tank Sewage treatment plant Centralized Decentralized Category Capacity(m3/day) Small to middle Application For household, building, housing complex, community, City covering with pipeline hospital, school, public toilet, etc. Target Black water & Gray water **Black water** Method Aerobic (plus Anaerobic) Anaerobic only Treated water - Good - Poor, BOD = 100mg/L - BOD < 20mg/L - Nitrogen and Phosphorous quality - Nitrogen & Phosphorous can be removed Clean discharge is discarded directly to the river, lake, - Dirty discharge is penetrated Discharge sea and so-on. into ground - Gray water is discarded without treatment Main body Civil structure constructed FRP manufactured in Civil structure constructed at Maintenance works Checking and adjustment, desludging, inspection, **Desludging only** changing spare parts (every 3 to 5 years) Long for planning, financing Total period for operation start construction Johkasou can be recognized as a "prefabricated small scale sewage treatment plant" in wastewater management



(Reference) Information of Johkasou


Installation records of Japanese Johkasou Overseas

- "Johkasou" is categorized as decentralized wastewater treatment system for domestic wastewater discharged by household, building and so-on."
- Johkasou have a combined purification structure capable of treating both night soil (black water) and miscellaneous wastewater (gray water)
- Johkasou attains high and stable performance as same as that of sewage treatment plant and it has been






6.5.3. 日本側環境省のセミナー発表資料(Legal System of Decentralized Domestic Wastewater Treatment Management in Japan including the Johkasou Act)



Approval process for types of Johkasou (Johkasou Act, Article 13) Inspection and Maintenance of Johkasou Parties intending to manufacture Johkasou in production plants shall obtain approval from the Ministry of Land. Infrastructure, Transport and Tourism (MLIT) for the type of Johkasou to be manufactured (does apply to test manufacturing) • This process is suitable to Performance Evaluation System Approval by the Model erformance Performance Put into Minister of Land. Approval by **Evaluation Test** Market Ensured Infrastructure, Transport Johkasou Act and Tourism Johkasou's Performance Evaluation System ✓ Detail of Johkasou's Moving Anaerobic Performance bedtank Sedimentation filter tank **Evaluation System** tank Sedimentation tank https://www.bcj.or.jp/upload/rating/bizunit/hyoutei/joushi_hyoukahouhou.pd Sample of Performance Evaluation Type Johkasou Registration process and qualifications system National qualifications Registration [Certified Johkasou Installation Worker]



MOEJ "Night Soil Treatment and Decentralized Wastewater Treatment System in Japan"

Prefecture

Instructions, advice, recommendations. etc.



company

Johkasou construction



Person certified to supervise Johkasou



Approval

Instructions, advice, recommendations. etc.



Johkasou desludging company

Registration


Prefecture Instructions, advice, or other recommendations,



Johkasou maintenance inspection company

[Certified Johkasou Operator]

Person certified to supervise Johkasou maintenance inspections



Training courses for Johkasou technicians

- Johkasou technicians should acquire extensive knowledge on not only wastewater treatment/johkasou. but also water environment conservation and public health.
- Curriculums for johkasou operator and johkasou installation worker are as shown below.

Johkasou Operator Johkasou Installation Worker by Article 45 by Article 42 Fundamental of johkasou 8 H • Fundamental of johkasou 8 H • Laws and regulations related with johkasou Laws and regulations related with johkasou 3 H Structure and function of johkasou 22 H • Structure and function of johkasou 15 H • Introduction to installation of johkasou 4 H • Management of johkasou installation 8 H Operation and maintenance of johkasou 30 H Introduction to O&M and desludging of johkasou Water quality management of johkasou 10 H 3 H Introduction to desludging of johkasou 2 H Total 80 Hours (13 Davs +Test 2 Hours



37 Hours

(5 Days)

+Test 2 Hours

6.5.4. JECES のセミナー発表資料 (Operation and maintenance, cleaning, inspection, license and sludge management for Johkasou)

OPERATION AND MAINTENANCE OF JOHKASOU SYSTEM IN JAPAN

Shinhi Kumokawa Ph.D


Center for International Cooperation of Johkasou System Japan Education Center of Environmental Sanitation (JECES

DEFINITION OF JOHKASOU O&M

Operations concerning to inspecting, maintaining and repairing johkasou (Johkasou Act, Article 2-3)



- Prevent loss of unit function and device breakdown
- · Maintain normal treatment performance
- · Promote proper regular desludging



DEFINITION OF JOHKASOU DESLUDGING

Desludging involves extracting the generated sludge and scum from johkasou and conditioning sludge in the tank, as well as cleaning tanks and auxiliary equipment.

(Johkasou Act, Article 2-4)



Recover/reset treatment performance of johkasou by removing sludge regularly

TECHNICAL STANDARDS FOR JOHKASOU O&M

- Technical standard for operation and maintenance
 (Article 2, Ordinance for Enforcement of Johkasou Act)
 This standard stipulates maintenance items and adjustment/repair items that must be carried out during operation and maintenance for every johkasou and the auxiliary device.
- Technical standard for desludging (Article 3, Ordinance for Enforcement of Johkasou Act)

Desludging standards stipulate items to be carried out for each unit and auxiliary device during desludging (e.g. methods for drawing out sludge)

Guidelines for johkasou operation and maintenance (Official notice)

These guidelines are issued by the Ministry of the Environment as specific policies for operations and maintenance technicians. They are designed to ensure that operation and maintenance as well as desludging are carried out optimally and in line with the specific characteristics of each treatment process.

ORDINANCE FOR ENFORCEMENT OF JOHKASOU ACT

(Rule of Using)

Article 1 Rules of using johkasou under the provisions prescribed in Article 3 paragraph 3 of Johkasou Act (hereinafter referred to as "Act") shall be as follows.

- (i) Water amount for flushing toilet shall be appropriate.
- (ii) Materials like insecticide, detergent, deodorant, fatty, disposable diaper, sanitary goods etc. which interfering with the normal functioning of johkasou, shall not be flowed.
- (iii) abbr.
- (iv) Industrial wastewater, rain water and other special wastewater shall not be flowed into johkasou.
- (v) Johkasou with electric equipment shall not be turned the power supply off.
- (vi) The top or around of johkasou shall has no structural object that may interfere with operation, maintenance and desludging of johkasou.
- (vii) The top of johkasou shall not be loaded which may interfere with its normal functioning.
- (viii) The opening part of aeratorshall not be blocked.
- (ix) When the failure or malfunction is found in the johkasou, it should be notified to the johkasou manager immediately.









GUIDELINES FOR JOHKASOU O&M

☐Technical standard for johkasou O&M, (1984, Johkasou Act)

- ➤ Guideline for O&M of Tandoku-shori johkasou (2000)
- ➤ Guideline for O&M of small-scale johkasou (1993)
- Guideline for O&M of medium/large-scale johkasou (2000)
- ➤ Guideline for O&M of N/P removal type johkasou (2000)
- ➤ Guideline for O&M of Membrane johkasou (2000)


☐ Technical standard for johkasou desludging (1984, Johkasou Act)



O&M FREQUENCY OF JOHKASOU


(Article 6-2, Ordinance for Enforcement of Johkasou Act)

Treatment process	Type/size of johkasou	Frequency
Separation-contact aeration process Anaerobic filter-contact aeration process	1. Johkasou with a size less than 20 PE	4 month
 Denitrification type anaerobic filter- contact aeration process 	2. Johkasou with a size more than 21 PE and less than 50 PE	3 month
Activated sludge process	(> 100PE)	1 week
Rotating biological contactor process Contact aeration process Trickling filter process	Johkasou with sand filter device, activated carbon adsorption device or flocculation tank (> 50PE)	1 week
	Johkasou with screen and flow equalization chamber (> 50PE)	2 week
	3. Other Johkasou (> 50PE) (without screen equipment, etc.)	3 month










6.5.5. フジクリーン工業株式会社のセミナー発表資料 (Structure, function and performance evaluation testing system for the Johkasou)



organic matter is decomposed


of nitrogen oxides take place.


and removed, and denitrification


materials and fat/grease

is decomposed and removed, and

nitrification of ammonia nitrogen take place







How to secure treatment performance at fields

Which system do you want to buy? Cheaper one is better. But... can meet discharge standard?? Cheaper one is better. But... can meet discharge standard??

Influent and effluent criteria for the testing

ntity)	1,000 for 5 PE ~	1,200	5	
	(Person Equivalent)	for 8 PE ~	Decide by manufacturer	Decide by manufacturer
BOD	180~220	150~750	100~300	Ave. 350
SS	145~175	150~750	100~350	Ave. 420
T-N	40~50	20~150	35 ~ 70	Ave. 70
BOD	20, 15, 10, 5	20、10	<c-bod> Monthly Ave: 25 Weekly Ave: 40</c-bod>	T
SS	20, 15, 10, 5	30、10	Monthly Ave: 30 Weekly Ave: 45	The effluent quality resulted in the testing is certified.
T-N	20, 15, 10, 5	15 (Nutrient Removal Type)	Removal rate ≧ 50%	11
	SS T-N BOD	SS 145~175 T-N 40~50 30D 20, 15, 10, 5 SS 20, 15, 10, 5	SS 145~175 150~750 T-N 40~50 20~150 30D 20, 15, 10, 5 20, 10 SS 20, 15, 10, 5 30, 10 T-N 20, 15, 10, 5 (Nutrient Removal	SS 145~175 150~750 100~350 T-N 40~50 20~150 35~70 30D 20, 15, 10, 5 20, 10 Monthly Ave: 25 Weekly Ave: 40 SS 20, 15, 10, 5 30, 10 Monthly Ave: 30 Weekly Ave: 45 T-N 20, 15, 10, 5 $\frac{15}{\text{(Nutrient Removal Type)}}$ Removal rate $\geq 50\%$

Conditions for performance testing

		Japan	Australia	The U.S.	EU (Germany)
Testing Conditions	Number of sites	6(indoor)	(outdoor)	10 (outdoor)	50 (outdoor)
	Wastewater	Actual + Artificial	Actual	Actual	Actual
	Temp. control	Temp. control 20°C 、13°C		No	No
	Start-up duration	Max. 8 weeks	Max. 8 weeks	Max. 3 weeks	Decide by
	Testing duration	Min. 8 weeks	34 weeks	26 weeks	38 weeks
	Peak inflow	Every day	Yes (as stress testing)	No	Every week @ Normal Testing
	Stress testing	Yes	Yes	Yes	Yes

FujiClean

10

Thank you!

6.5.6. クボタ浄化槽システム株式会社のセミナー発表資料 (Estimation method of Population Equivalent (PE))

JIS ESTIMATION OF POPULATION FOR JOHKASOU

浄化槽の人員算定(JIS A 3302-2000)

JSA (Johkasou System Association) KJS (KUBOTA JOHKASOU SYSTEM)

Yoshito Kitai

2023/12/19

JIS A 3302-2000

Estimation of population for Johkasou

1 P.E. = 200L/day, 40g BOD/day, BOD 200mg/L

Large categories(Detail categories(No.of equation))

- 1. Public hall (Theater, etc. (3))
- 2. Residence (Apartment, etc. (6))
- 3. Accomodation(Hotel Motel, etc. (4))
- 4. Medical facility (Clinic, etc. (5))
- 5. Shop(Shop, Restaurant, Café etc. (6))
- 6. Amusement facilities (Disco, Amusement Park etc. (13))
- 7. Parking (Highway rest area, gas station etc. (7))
- 8. School (Elementary school, Collage, Library, etc. (3)
- 9. Office (with canteen, without canteen. (2))

10. Workshop (facory, Laboratory, etc. with canteen,

without canteen(2))

11.Others (Public toilet, etc. (6))

Total 11 large categories, (Detail categories 57 equations)

IIS A 3302-2000

Estimation of population for Johkasou (Decentralized STP)

1. Prescribe standards for calculating the number of people of the Johkasou based on the purpose of the building.

(建築物の用途別による浄化槽の処理対象人員算定基準について規定する)

2. The criteria for calculating the number of people of the Johkasou are as shown on the table. Specified in total 11 large categories, 57 equations. Reference values for water volume per calculation unit and BOD and influent time is also shown. Discharging time is required for Eq. tank design. However, if the regulations clearly do not match the actual situation, the number of personnel may be increased or decreased. (建築物の用途別による浄化槽の処理対象人員算定基準は、表の通りとする。

Total 11 large categories, 57 equationsで規定する。算定単位当たり水量、BODそれから排水時間も参考値で示されています。排水時間は調整槽の大きさの設計で必要です。

ただし、規定が明らかに実情にそぐわない場合は、人員を増減できる。)


3. If the same building has two or more different uses, each calculated by adding the term for building use.

同一の建築物に2つ以上の異なった建築用途がある場合は、それぞれの 建築用途の長さ加算して算定する。)

2. 1.Residence 住宅

[Equation]

If total floor area A (m2) <130m2, Johkasou capacity (P.E.) shall be 5 P.E.




2.2. Apatment 共同住宅

5. Shop 店舗関連

①Shop/market 店舗、マーケット 【Equation】 Johkasou capacity (P.E.) n= 0.075 x A (A (m2) :total floor area)

②Restaurant(General) 飲食店(一般) 【Equation】

Johkasou capacity (P.E.) n= 0.72 x A



4. Medical Facilities 医療施設関係

Example

Large hospitals with commercial kitchens or laundry facilities

[Equation]

B(beds)<300: n=8 x B (p.e.)
B(beds)≥300: n=11.43 x (B-300) + 2.400 (p.e.)

Ex. If B=100 beds
n=8×100 = 800 p.e.人槽
Q=0.125m3/p.e./d x 800 p.e. = 100 m²/d
BOD=320mg/L

9. Office 事務所関連

Office with kitchen 事務所【Equation】

(With kitchen 厨房施設有り) Johkasou capacity (P.E.) n= 0.075 x A

(A (m2) :total floor area)

(Without kitchen 厨房施設無し) Johkasou capacity (P.E.) n= 0.06 x A

Ex. 400m with kitchen

 $n = 0.075 \times 400 = 30$ p.e. 人槽 Q = 0.2m3/p.e./d x 30p.e = 6 m3/d BOD = 200mg/L



∞

10. Workshop 作業場関係

Factory, laboratory 工場、研究所(厨房施設有り)

(With kitchen 厨房施設有り)

[Equation]

Johkasou capacity (P.E.) n= 0.75 x P

(P: Full number (person)※定員)

(Without kitchen 厨房施設無し)

Johkasou capacity (P.E.) $n = 0.3 \times P$

Ex. P=100 persons with kitchen 厨房有

 $n = 0.75 \times 100 = 75$ p.e. 人槽

 $Q = 0.133 \text{ m}3/\text{p.e.}/\text{d} \times 75 \text{ p.e.} = 10 \text{ m}3/\text{d}$

BOD=300mg/L



Application Overseas

海外での適応

The JIS calculation standards are determined statistically based on survey (took several years for dozens of JSA companies) data such as drainage volume, number of population, and total floor area for actual construction purposes in Japan. It is reviewed and revised from time to time in response to changes in lifestyle.

JISの算定基準は、日本での実際の建築用途の排水量、使用人員、延べ床 面積などの調査データ(JSA数十社で数年かかった)から統計的に定めてい るもの。時折生活様式の変化などに合わせ、見直し改定が行われている。

●When overseas, estimation of population should be done according to the lifestyle of the country. 海外では、その国の生活様式に合わせた算定を行うことが望ましい

11. Others その他施設

Ex. Public Toilet 公衆便所

[Equation]

Johkasou capacity (P.E.) $n = 16 \times C$

(C: Number of lavatory basin 総便器数)

Ex. C=10 Public toilet 便器10個の公衆便所 n = 16 × 10 = 160 p.e. 人槽(24㎡/日) Q = 2.4m3/set/d x 10 sets = 24 m3/d

BOD = 260 mg/L



6.5.7. 株式会社ダイキアクシスのセミナー発表資料 (Installation work of Johkasou)

Johkasou - Installation



OUTLINE

- Legal frame work of Johkasou installation
- Johkasou installation works

Legal Framework for Johkasou Installation

The following items are listed in the Johkasou Act with regard to installation

Notification

Submit a notification of Johkasou installation to the competent authorities prior to construction

Installation

- Construction can only be performed by a business office registered in the prefecture that has jurisdiction over the area where the installation work is to be performed
- Installation or supervision by a national qualified Johkasou installer

Johkasou Installation Flow

1	Prior On-Site Survey Check installation location and delivery		
2	Application for installation	Submit notification of Johkasou installation	
3	Temporay work	Site preparation	
4	Excavation	Excavate to required depth	
5	Foundation	Make a reinforced concrete slab	
6	Installation	Install Johkasou on the base slab Fill the Johkasou with water	
7	Filling water		
8	Backfilling	Backfill around Johkasou with sand	
9	Piping work	Connect each piping	
10	Electrical work	Install blower, pump, control panel and so on	
11	Upper conclete work Make a RC slab on Johkasou		
12	Trial operation Check Johkasou and equipment fur		
13	Cleaning & Handover	Explain Johkasou to users	





Johkasou Installation - Prior On-Site Survey

5

Purpose

To check the site conditions prior to Johkasou installation and ensure smooth installation

Check Point -

Sufficient area to install a Johkasou Location and depth of inlet pipe Treated water discharge point Existing pipe and cable location Ground water level Special installation or not Johkasou delivery route Electricity and tap water availability Blower and control panel location Maintenance workability





Johkasou Installation – Temporay work

_/

Purpose

Prepare site for excavation can be done without problems Measure and determine the area to be excavated

Description -

Clearing the ground before installation Decide where to install Johkasou External inspection of the Johkasou





Johkasou Installation – Application for Installation 6

Purpose

Ensure that Johkasou is properly install Ensure Johkasou model, capacity, install date and builder

Documents

Notification of installation of a Johkasou
Notification of change of Johkasou
Johkasou card
Johkasou use start-up report
Johkasou owner change report
Notification of discontinued use of Johkasou
Notification of Johkasou out of use
Notification of Johkasou re-use start-up
Technical operator change report



 $https://www.kankyo.metro.tokyo.lg.jp/resource/general_waste/septic_tank/septic_tank_law.html\\$



Johkasou Installation - Excavation

8

Purpose

For underground installation, excavate as per the drawing Underground installation allows for effective use of space

Description -

Excavate to the depth required in drawing
Use retaining walls if necessary
Use submersible pump if groundwater spring



Point

Excavate about 5 cm larger than the size of the bottom slab to make it easier to work on







Johkasou Installation - Foundation 1

9

Purpose Use rubble stones to harden the foundation

Description -

Make sure it has the necessary square footage Place rubble stones of unequal size Fill in the gaps with sand Stamp them sufficiently with a rammer



Point —

Thickness shall be in accordance to drawing Usually 100 mm or 150 mm (T-0)





Johkasou Installation - Installation

11

Purpose Install Johkasou on base slab

Description -

Visual inspection of Johkasou Clean base slab (small stones, etc.) Lift Johkasou according to the manual Place Johkasou in the center of base slab Check Johkasou is installed horizontally Install wire to prevent raising by groundwater





Johkasou Installation - Foundation 2

10

To install Johkasou horizontally Prevent Johkasou from being raised by groundwater

Description —

Place concrete 50mm thick on the rubble stone according to the drawing Make a temporary framework with the specific dimensions Rebar arrangement according to the drawings

Install anchors according to the drawing

Cast concrete with surface tolerance of ± 2.5 mm/1m









Johkasou Installation - Filling Water

12

To protect Johkasou from soil pressure To prevent the Johkasou from shifting during backfilling

Description -

Check Johkasou is secured with wires Fill Johkasou with tap water Make sure Johkasou is not leaking water







Johkasou Installation - Backfilling

13

Protects Johkasou from UV light Fill in gaps for easier maintenance

Description

Ensure Johkasou is filled with water Ensure backfill sand is free of stones and gravel Cover Johkasou to prevent sand from getting in Backfill and water tightening in three steps







Johkasou Installation – Electrical work

15

Purpose Install blower, pump, control panels...

Description

Install a blower in a well-ventilated place Avoid direct sunlight on the blower Blower should be installed on flat concrete Provide grounding works as required



Point

Air piping should be kept as sand-free as possible The platform for the blower should be about 200mm higher than the GL. Use header pipes if there is more than one blower



Johkasou Installation - Piping Work

Connect inflow pipe, effluent pipe Connect blower and Johkasou

Description

Connect the inflow pipe and Johkasou Connect the effluent pipe and Johkasou Connect the blower and Johkasou with piping Air pipes shall be 10m in length and within 5 bends Install an exhaust pipe for surrounding area Install pipe supports if necessary



Point

Be careful not to allow sand to enter the piping Check drawings for piping sizes and install



AXIS

16

14

Johkasou Installation – Upper Concrete Work

To prevent rainwater from entering the tank For easier maintenance works

Description

Cast upper slab in same procedure as base slab Note that the reinforcement is different from the base slab









Clean around Johkasou and

Hand over the Johkasou to its user

Purpose Check for proper operation through a trial operation


Description

Check piping joint condition

Check for air leakage

Check if moving bed medias are moving well Check there is no difference in water level Check if the circulation volume can be set







Description -

Clean up sand and trash

Report to the user that the construction has been completed Inform users about proper use of Johkasou and precautions to be taken





Johkasou Installation Reference

19

Underground installation



Above ground installation





Half underground installation





References of Special Installation







Features of Johkasou Installation

21

Above ground	Under ground	
Short construction period	Easy maintenance	
Save the cost of construction	Utilization of space	
Possible to relocate in the future	Ultraviolet no effect	

We can chose some installation due to the site condition.



6.6. セミナーにおける質疑応答

No.	Questioner	Question/Comment	Answerer	Answer
1.	The	NMCG の発表における	NMCG	我々はリアルタイムで状況を把握できるオンラインのモニタリングシステムを所
		Namami Gange Programme に		有している。現在 200 の Sewerage Treatment Plant (STP)に本システムが導入され
	of Tokyo	ついて、多くのプロジェクトが並		ている。更に、流域内の残り 200 の STP へ本システムの新規導入を検討している。
	Dr. Kasuga	行して進行しているかと思うが、		本システムは事務所にてモニタリング可能である。15分ごとに送られてくるデータ
		どのようにして各プロジェクトを		によって現状を把握している。
		評価するのか聞きたい。河川のモ		また、同様のシステムをガンジス川流域に 75、その他の場所に 110 導入する予定
		デルがあるのか。Sewerage		である。本システムにより下水の状況及び水質の関係をモニタリングしている。取
		Treatment Plant(STP)の建設前		得したデータの集計は、取得月の翌月に公表している。
		後でどのように変化したのか。		水質は1-5段階に分けられており、1は非常に不良、5は非常に良好というのを示
		With respect to the Namami		す。結果については、13枚目のスライドに記載した2014-2015年及び2022年の各
		Gange Program in NMCG		年の状況を比較したデータを見てほしい。
		presentation;		We have an online effluent quality monitoring system that allows us to
		I believe that many projects		understand the situation in real time. This system is currently installed in 200
		are progressing in parallel, but I		Sewage Treatment Plants (STPs). We are also considering introducing this
		would like to know how you evaluate the effect of each		system to the rest 200 STPs in the basin. This system can be monitored at the
		project.		office. The current situation is monitored by the data sent every 15 minutes.
		Is there a water quality river		We also introduce the similar Real Time Water Quality Monitoring Stations to
		model? How the situation has		75 locations of Ganga river basin and will introduce to other 110 locations of
		been changed before and after		other rivers of the basin. This system monitors the relationship between sewage conditions and water quality of the Ganga river. The aggregated data is
		the Sewerage Treatment Plant		published in the month following the month in which it was obtained. Water
		(STP) was constructed?		quality is graded from Priority 1 to 5, with 1 being very high polluted and 5 being
		,		less polluted good. Regarding the outcome, please see the slide No.13 of
				comparison of data of each state in 2014-15 and 2022.
2.	The	Q1 の回答によってモニタリン	NMCG	Swachh Bharat Mission - Gramin(SBM-G) という村単位の液体廃棄物のイン
	University	グの方法は理解した。ガンジス川		フラを設置するというプログラムが別途あり、人口 10,000 人以下の小さな村などの
	of Tokyo	の水質のモデルを作成して水質の		排水管理もカバーすることになっている。
	Dr. Kasuga	監視をより効率的に実施するのが		しかし流域保全を目的とする Namami Gange Program (NMG)では、対象地域内
		良いと思う。		に人口 10,000 人以下の小さな村が多く含まれている。このため、NMG によって導
		追加の質問で、スライド P.16 に		入された最小の汚水処理施設の容量は 10 m³/日で、最大の施設では 565,000 m³/日の
		ある国家水政策(National Water		下水処理場(JICA による支援)である。2019 年に施行された SBM は、2012 年の
		Policy)には、人口が 10,000 人以		国家水政策を補完することになっている。
		上の地域には STP を設置しなけ		

No.	Questioner	Question/Comment	Answerer	Answer
		ればならないとあるが、10,000 人以下の地方や農村などについて は言及されていない。国家水政策 にはどの程度の人口が含まれない のか? Based on the answers to Q1, I understood the monitoring method. I think it would be a good idea to create a water quality model of the Ganges River and monitor water quality more efficiently. In an additional question, the National Water Policy on slide P.16 states that STPs must be installed in areas with a population of 10,000 or more, however, it does not mention to the rural area or small villages with a population less than 10,000. How much of the population is NOT included in national water policy?		There is a separate program called Swachh Bharat Mission - Gramin (SBM-G) to set up village-based liquid waste infrastructure, which will also cover wastewater management in small villages with a population of less than 10,000. However, the Namami Gange Program (NMG), of which purpose is water environment conservation, includes many small villages with a population of less than 10,000 people within the target area. Therefore, the smallest sewage treatment facility installed by NMG has a capacity of 10 m3/day, and the largest facility is a 565,000 m3/day sewage treatment plant (supported by JICA). The SBM, which came into force in 2019, is supposed to complement the 2012 National Water Policy.
3.	NMCG	現在、浄化槽の排水を貯留する	Mr. Sato	浄化槽の排水については基本河川に放流しているため、貯留しているという実績はないと思われる。 浄化槽の処理水の再利用について、MOEJ 主催で 11 月 28 日にワークショップを 開催した。JECES のホームページに発表資料を掲載しているため、後ほど URL を 送付する。 As wastewater from Johkasou is generally discharged into rivers, I think there would be no cases of it being stored. A workshop was held on 28 th November, 2023 organized by MOEJ regarding the reuse of effluent from Johkasou. The presentation materials are posted on the JECES homepage and seems to be a reference for your question. JECES will send you the URL later.

C	C)
۸	٠	0

No.	Questioner	Question/Comment	Answerer	Answer
4.	NMCG	ライフサイクルコスト(LCC)を教えてほしい。例えば耐用年数が15年の場合はどの程度費用がかかるか。 I would like to know the life cycle cost (LCC) of the Johkasou . For example, if the service life is 15 years, how much will it cost?	DAIKI AXIS INDIA PVT.LTD. Mr. Kamal Tiwari	現時点での私の考えでは、BOD 20 mg/L かつ容量が 1t/day の場合、最初に発生する費用(CAPEX)は 1.6Lakhs(ラーク、2024年2月7日時点で約284,800円)であり、他に現場の状況に応じて追加費用(15,000-22,000ルピー)が必要になる。また、清掃、電気料金、消毒剤などメンテナンス費用(OPEX)が年間約7,000ルピーで、利用者が負担する。維持管理契約では維持管理の頻度も決めており、付帯設備がある場合はその維持管理費用も利用者が負担している。 My current thinking is that if the effluent BOD is 20 mg/L or less and the capacity is 1 t/day, the initial cost will be 1.6 Lakh, and in addition, maintenance costs will be incurred. Also, additional costs (20,000-25,000 rupees) will be required depending on the site situation. In addition, maintenance costs (OPEX) such as sludge cleaning (desludging), electricity charges, and disinfectants are approximately 7,800 rupees per year, which is to be paid by the users. The maintenance contract also determines the frequency of maintenance, and if there are incidental facilities, the user is also responsible for the maintenance costs.
			DAIKI AXIS INDIA PVT.LTD. Mr. Rio Waza	OPEX に関して特に電力消費量に差があり、Membrane Bioreactor(MBR:膜分離活性汚泥法)では膜交換費用も必要になるため、かなり高額になる。しかし、浄化槽で主に採用されている MBBR(Moving bed biofilm reactor)または FBBR(Fixed Bed Biological Reactor)システムでは担体を交換する必要が無いので、15 年間のライフサイクルコスト(LCC)も低くなることが想定される。使用開始から 4-5 年経過した際はポンプやブロワの交換が必要となり、それらが LCC に大きな影響を与えるのではないかと考えている。 Regarding OPEX, there is a particular difference in power consumption, and Membrane Bioreactor (MBR; membrane separation activated sludge method) requires also membrane replacement costs, and making it quite expensive. However, in the MBBR (Moving bed biofilm reactor) or FBBR (Fixed Bed Biological Reactor) systems that are mainly adopted in Johkasou, there is no need to replace the media, so the 15-year life cycle cost (LCC) can be lower. The pumps and blowers will need to be replaced after 4-5 years of use, and we believe that these are main parts of LCC.

•	٥	,
^	•	٠
(J

No.	Questioner	Question/Comment	Answerer	Answer
			Arvind	6年ほど本業務に従事し150基以上の浄化槽を導入した中で得た知見に基づく
				と、処理容量が大きくなればなるほど O&M 費用は相対的に下がると考えている。
			Mr. Amit	浄化槽をインドで利用すると、他の標準的な STP の維持管理費の 70-80%まで低減
			Shah	できると思っている。
				また、CAPEX についても言及させていただく。例えば 10 ㎡/日の浄化槽では 7.5
				~8 Lakhs (2024年2月7日時点で約1,335,000円)、100 ㎡/日の浄化槽では35~
				40 Lakhs 程度である。更に、浄化槽内部で利用する担体の種類、処理容量、要求さ
				れる処理水のレベル (インドでは放流水の BOD が 30-5mg/L と幅がある) によって
				も変化してくる。また、浄化槽システムを設計する際、フィルターシステムや貯留
				槽を追加するか、どのようなタイプの制御盤を利用するか、どこから電源を引き込
				むか、等の条件によっても CAPEX は変化してくる。このように、例えば 10 ㎡/日
				の浄化槽でも、OPEX は 7.5 Lakhs から 15 Lakhs と変動する。
				Based on the knowledge I've gained from working in this business for about 6
				years, I believe that OPEX will decrease relatively as the treatment capacity
				increases. We believe that using Johkasou in India can reduce maintenance costs
				by 70-80% of other conventional STP system.
				I would also like to mention CAPEX. For example, a 10 m3/day Johkasou system
				costs 7.5 to 8 Lakhs, and a 100 m3/day Johkasou costs about 35 to 40 Lakhs.
				Furthermore, CAPEX also changes depending on the type of media used inside
				the Johkasou, the treatment capacity, and the required level of treated water (in
				India, the BOD of effluent water varies from 30 to 5 mg/L). And, when designing a Johkasou system, CAPEX will also change depending on conditions such as
				whether to add a filter system or storage tank, what type of control panel to use,
				where to draw power from, etc.
				Thus, for example, even for a Johkasou of 10 m3/day, the OPEX varies from 7.5
				Lakhs to 15 Lakhs.
5.	NMCG	浄化槽に係る費用と他の分散型	Indian	回答者のお話のとおり、集中型処理システムに係る費用と、浄化槽に係る費用を
		汚水処理施設に係る費用を比較し	Institute of	比較すると、浄化槽が割高になる。例えば1㎡当たりの処理単価は下水道では5ル
		たいため、もし資料等の比較材料	Technology-	ピー、浄化槽では20ルピー程であると思う。しかし、浄化槽は集中型処理施設が設
		をどなたかお持ちであれば教えて	Roorkee	置できないようなケース、例えば、小さな集落やコロニーに、小規模下水道システ
		ほしい。	Prof.	ムとして、または戸建て住宅に導入されることを考慮すべきである。一方、こうい
		I would like to compare the	Kazmi	ったケース以外では下水道など集合型処理の方が、CAPEX,OPEX 含め処理コスト
		costs associated with Johkasou		が安くなるのは明白である。よって集合処理が導入できない場合に浄化槽を導入す
1		and other decentralized sewage		べきである。

θ
4

No.	Questioner	Question/Comment	Answerer	Answer
		treatment facilities, so if anyone		As other respondents have said, if you compare the cost of centralized STP and
		has any materials for		the cost of a Johkasou, it seems that the Johkasou will be more expensive. For
		comparison, please let me know.		example, I think the treatment unit cost per cubic meter is about 5 rupees for
				sewers and 20 rupees for Johkasou. However, Johkasou should be considered for
				installation in cases where it is not possible to install centralized treatment
				facilities, for example in small settlements or colonies, as small-scale sewerage
				systems or in individual houses. On the other hand, in other than these cases, it
				is clear that the centralized treatment such as sewage is cheaper. If centralized
				treatment is not possible to install, Johkasou should be installed.
			DAIKI	分散型/集合型で公平な比較をする必要があると考えている。集合型処理施設を設
			AXIS	置するとなった場合、大掛かりなパイプの敷設や近隣への影響を考慮しなければな
			INDIA	らない。我々は幸いにも分散処理/集合処理の専門家もおり、分散処理に関してはデ
			PVT.LTD.	ータとして利用可能な実例を多く把握している。また、NMCG は分散処理/集合処
			Mr. Kamal	理それぞれのデータを所有していると認識している。よってこれらデータを基に比
			Tiwari	較すればより深く探求することが出来ると思う。
				I think it is necessary to make a fair comparison between decentralized and
				centralized system. When installing a centralized treatment facility,
				consideration must be given to the installation of large-scale pipes and the
				impact on neighboring areas. Fortunately, we also have experts in decentralized
				and centralized system, and we have many examples of decentralized system
				that can be used as data. In addition, I think NMCG own data for both
				decentralized and centralized system. Therefore, I think it would be possible to
				study more deeply by comparing based on these data.
			Arvind	Dr. Kazmi そして Mr. Kamal がお話しされたことに追加させていただく。
			Envisol ltd	同等の処理容量の分散型汚水処理施設を比較することも重要であると考えてい
			Mr. Amit	る。Dr. Kazmi が述べたように、処理容量によって LCC も変化してくる。そこで、
			Shah	例えば、200 m³/日の施設を1つ例として挙げて、実際に分散型汚水処理施設の市場
				で流通している技術、例えば MBR システム、標準活性汚泥法、他のシステムなど
				と5年間の運転費用を比較する、などである。単純に分散型/集合型汚水処理施設を
				比較するのは困難である。Dr. Kazmi にはこういった比較研究をしていただきデー
				タを共有していただきたい。
				I would like to add to what Dr. Kazmi and Mr. Kamal said.
				I also believe it is important to compare decentralized wastewater treatment
				facilities with equivalent treatment capacity. As Dr. Kazmi mentioned, LCC also
				changes depending on the treatment capacity. For example, I think it would be
			<u> </u>	changes depending on the treatment capacity. For example, I think it would be

		(,
1	•	7	
١		,	ı

	better to compare the facility with a treatment capacity of 200 m3/day as an
DA AX IN PV Mr	example, on the operating costs for 5 years with different technologies such as the MBR system, conventional activated sludge method, and so on (technologie actually distributed in the market for decentralized wastewater treatment facilities). It is difficult to simply compare decentralized/centralized wastewater treatment facilities. I would like Dr. Kazmi to conduct this kind of comparative research and share the data. Ello 議論にコメントさせていただく。集合処理と分散処理ではそれぞれメリット・デメリットがあるが、加えて、長期的な視点で両者を評価することも必要であると思われる。例えば、集合処理では、40年後、50年後、莫大なキャピタルが必らと思われる。例えば、集合処理では、40年後、50年後、莫大なキャピタルが必らなり、修復工事などに多くの費用が必要になる。よって LCC 分析を行う際はイド国内または対象地域にどの設備が適しているか、長期的な視点で検討する必要があると思われる。 I would like to comment on the above discussion. Centralized system and decentralized system each have different advantages and disadvantages, but it is also necessary to evaluate both from a long-term perspective. For example, centralized system will require a huge amount of capital 40 to 50 years later, due to for repair work. Therefore, when conducting LCC analysis, it is necessary to consider from a long-term perspective which facilities are suitable for India or the target region. IIKI

6.7. セミナー終了後に日本側会議体メンバーから受領した質問

No.	Questioner	Question/Comment				
1.	MOEJ	Shri Dheeraj Joshi のプレゼン P.18 には、NMCG プロジェクトとして浄化槽 3 件が設置されているとのことですが、稼働				
		状況を教えていただきたい。処理水は再利用されていますか?また、NMCG はこの3件をどう評価していますか(良い点、				
		良くない点を含めて教えていただければと存じます)?				
		In the presentation from Shri Dheeraj Joshi, on page 18, it has introduced that 3 (three) Johkasous were installed as				
		part of the NMCG project.				
		I would like to know the operating status of these Johkasous.				
		Is treated water (effluent) reused? Also, how would NMCG evaluate these three Johkasou (I would appreciate if you				
0	MODI	could tell me the good and bad points)?				
2.	MOEJ	Shri Dheeraj Joshi のプレゼン P.19 には、分散型処理技術が紹介されていますが、これらの施設の水質や機械等の稼働に				
		関するトラブル等、もし困っていることがありましたら教えていただきたい。				
		In the presentation from Shri Dheeraj Joshi, on page 19, decentralized treatment technology is introduced. If there is any trouble regarding effluent water quality or operation of machinery etc. at these facilities, please kindly let us know.				
3.	MOEJ	インド側として今回のセミナー開催の意義は何か。また、何が有益で、インドの水環境改善に今回の内容をどのように役立				
J.	MOES	てるか、現時点での見解を伺いたい。				
		For the Indian side, what was the significance of holding this time of seminar?				
		Additionally, I would like to hear your current views on what is useful and how the contents of these presentation can				
		be used to improve India's water environment.				
4.	MOEJ	今回のセミナーの内容をどう評価しましたか?もし改善点等がありましたら教えてください。				
		How did you evaluate the content of this seminar?				
		Please let us know if there are any improvements.				
5.	Dr. Kawamura	河川水質のモニタリングにおける水質項目を教えてもらいたい。				
		BOD が含まれているとしたなら、15 分ごとのモニタリングはどのようにして行っているのか。				
		Would you tell me the items for monitoring of the river water quality?				
		In addition, if BOD is included in those items, how the monitoring is been conducted every 15 minutes?				
6.	Dr. Kawamura	浄化槽の処理水質に対して想定している項目と水質値はどのようなものか。また、管理主体は誰になるのか。どちらも下水				
		道との対比で回答してもらいたい。				
		What items and the water quality values are assumed for the effluent quality of the Johkasou?				
		Also, who will be the managing entity of Johkasou in India?				
		Would you answer both questions by comparing them with sewagetreatment plant?				